

DTFS 6021 | 31 | 41

Green Series



- + Flexible mounting
- + Conformity with F-Gas Regulation
- + Increased energy efficiency

Variable integration through
space-saving housing design

DTFS Green Series: Product benefits at a glance



Flexible mounting

- Fully integrable in the door or side
- Suitable for external mounting on the door or side installation
- Suitable for narrow enclosure designs
- Quick and easy installation: uses the same cut-out

Environmentally friendly

- In accordance with the "F-Gas" regulation:
Use of R-513A, a low GWP refrigerant
- Maximum energy efficiency: EER > 2
- Low amount of refrigerant contained

Various applications


- Smaller dimensions: Cooling units fit into narrow cabinets (e.g. door width 400 mm)
- Enables space-saving machine planning & construction
- 400V and 115V versions do not require additional space due to the integrated transformer



Controller

The DTFS series is equipped with two variants of controllers - Display and LED variant. Both variants have an energy-saving mode with a new algorithm that does not require an additional temperature sensor.

Display





Shows alarms, temperatures, energy-saving mode and error codes via the display menu.

LED



Indicates normal operation, energy-saving mode and errors via colored LED light.

DTFS Green Series: Three performance classes - two sizes

PRODUCT	DTFS 6021	DTFS 6031	DTFS 6041
DATA			
Cooling capacity @35/35 230 V 50 Hz	370 W	570 W	870 W
Dimensions			

DTFS Green Series: Comparison 6000 vs 9000 series

	Cooling capacity @35/35 230 V 50 Hz		EER @230 V 50 Hz		Amount of refrigerant R513A / R134a	
COMPARISON						
DTFS 6021	370 W	+ 16 %	2,1	+ 51 %	150 g	- 57 %
DTFI 9021	320 W		1,39		350 g	
DTFS 6031	570 W	+ 12 %	2,3	+ 28 %	180 g	- 28 %
DTx 9031	510 W		1,8		250 g	
DTFS 6041	870 W	+ 0 %	2,1	+ 27 %	225 g	- 44 %
DTx 9041	870 W		1,66		400 g	

Easy maintenance



- Direct access to control unit and condenser
- Simple replacement of fans due to pre-assembled spare parts
- Quick access to the external heat exchanger enables fast cleaning

Pfannenberg – Protecting People, Machines and the Environment

Vision

One Pfannenberg for Our Customers – We are constantly working to develop the best and most sustainable products for you.

Global availability

Neun Pfannenberg Standorte in:

Hamburg (DE) - HQ	Suzhou (CN)
Rotherham (UK)	St. Petersburg (RU)
Fidenza (IT)	Indaiatuba (BR)
Lancaster N.Y. (US)	Łódź (PL)
Singapore (SG)	

In addition, we at Pfannenberg work in partnership with sales representatives and regional agents worldwide in order to be able to present our product portfolio to you.

Sustainability

We combine the flexibility of a family-run company with the agility of a global corporation. In our work, we attach great importance to combining tradition with innovation in order to be able to act in a future-oriented manner.

Would you like to find out more about our F-Gas compliant cooling units?

Please contact your Pfannenberg contact person or write our [Product Management](#) a message!