



# 7/8" MIN Series Size I Accessories

## 2, 3 & 4 Conductor MIN Series Size I Accessory Cables



100' Cables | Raw Cable Spools

| # of Conductors | Color Code                                                                  | Wire AWG | Voltage Rating | Features                             | Jacket Color | Part Number     |           |
|-----------------|-----------------------------------------------------------------------------|----------|----------------|--------------------------------------|--------------|-----------------|-----------|
|                 |                                                                             |          |                |                                      |              | 100' Cable      | Spool     |
| 2               | North American<br>White<br>Black                                            | 16 AWG   | 600V           | PVC<br>STOOW<br>9.4mm OD (0.37" OD)  | Yellow       | MIN-2CBL-C      | 10A0001-* |
|                 |                                                                             |          |                |                                      | Black        | MIN-2CBL-C-B    | 10B0001-* |
| 3               | North American<br>Green/Yellow<br>Black<br>White                            | 16 AWG   | 600V           | PVC<br>STOOW<br>10mm OD (0.39" OD)   | Yellow       | MIN-3CBL-C      | 10B0001-* |
|                 |                                                                             |          |                |                                      | Black        | MIN-3CBL-C-B    | 10BB001-* |
|                 |                                                                             |          |                | PUR<br>AWM<br>10mm OD (0.39" OD)     | Yellow       | MINP-3CBL-C     | 10BP001-* |
|                 |                                                                             |          |                |                                      | Black        | MINP-3CBL-C-B   | 10BP001-* |
|                 |                                                                             | 18 AWG   | 300V           | TPE<br>SEOOW<br>10mm OD (0.39" OD)   | Yellow       | MINW-3CBL-C     | 10BW001-* |
|                 |                                                                             |          |                |                                      | Black        | MINW-3CBL-C-B   | 10BW001-* |
|                 | North American<br>Auto Color Code<br>Green/Yellow<br>Red/Black<br>Red/White | 16 AWG   | 600V           | PVC<br>STOOW<br>10mm OD (0.39" OD)   | Yellow       | MIN-3ACBL-C     | 10L0001-* |
|                 |                                                                             |          |                |                                      | Black        | MIN-3ACBL-C-B   | 10LB001-* |
|                 |                                                                             | 18 AWG   | 300V           | PVC<br>SJTOOW<br>8.5mm OD (0.33" OD) | Yellow       | MIN-3ACBLX-C    | 10LX001-* |
|                 |                                                                             |          |                |                                      | Black        | MIN-3ACBLX-C-B  | 10LBX01-* |
|                 | European<br>Green/Yellow<br>Brown<br>Blue                                   | 18 AWG   | 300V           | PVC<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MINE-3CBLX-C    | 10BXE01-* |
|                 |                                                                             |          |                |                                      | Black        | MINE-3CBLX-C-B  | 10BXEB1-* |
|                 | European Cenelec<br>Black<br>Brown<br>Blue                                  | 18 AWG   | 600V           | PVC<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MINC-3CBLX-C    | 30BX001-* |
| 4               | North American<br>Black<br>White<br>Red<br>Green/Yellow                     | 16 AWG   | 600V           | PVC<br>STOOW<br>10.8mm OD (0.42" OD) | Yellow       | MIN-4CBL-C      | 10C0001-* |
|                 |                                                                             |          |                |                                      | Black        | MIN-4CBL-C-B    | 10CB001-* |
|                 |                                                                             | 18 AWG   | 300V           | PVC<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MIN-4CBLX-C     | 10CX001-* |
|                 | European Cenelec<br>Brown<br>White<br>Blue<br>Black                         | 18 AWG   | 600V           | PVC<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MINC-4CBLX-C    | 30CX001-* |
|                 |                                                                             |          | 300V           | PUR<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MINCP-4CBLX-C   | 30CXP01-* |
|                 |                                                                             | 18 AWG   | 300V           | TPE<br>AWM<br>7.4mm OD (0.29" OD)    | Yellow       | MINCW-4CBLX-C   | 30CWX01-* |
|                 |                                                                             |          |                |                                      | Black        | MINCW-4CBLX-C-B | 30CWX01-* |

\* Standard raw spool lengths are 0250, 0500, 0750 & 1000 feet. Consult factory for other lengths.

Cable Construction subject to change without notice.

Lengths in feet. Standard cable length is 100 feet. Consult factory for other lengths.

A

MIN Series Size I Cordsets