




Ethernet Series Accessories

8 Conductor Ethernet Series Accessory Cables



100' Cables | Raw Cable Spools | CAT5e | Twisted Pairs

# of Conductors	Color Code	Wire AWG Rating	Features	DC Resistance	Continuous Flex	Part Number	
						100' Cable	Spool
8	White/Blue White/Brown Brown Orange White/Green White/Orange Blue Green	24 AWG Stranded 600V	Teal PVC AWM CMX/CMR -20°C to +80°C 6.4mm OD (0.25" OD)	≤ 89 Ω/Km	No	MDE45-8CBL-C	60G0001-*
		24 AWG Stranded 600V	Teal PVC AWM With Foil/Braided Shield -20°C to +80°C 7.6mm OD (0.30" OD)	≤ 89 Ω/Km	No	MDE45B-8CBL-C	60GS001-*
		24 AWG Stranded 300V	Teal PUR AWM -40°C to +80°C 6.3mm OD (0.25" OD)	≤ 91 Ω/Km	Yes	MDE45P-8CBL-C	60GP001-*
		26 AWG Stranded 300V	Teal PUR CMX With Foil/Braided Shield -40°C to +75°C 6mm OD (0.24" OD)	≤ 140 Ω/Km	Yes	MDE45PB-8CBL-C	60GSP02-*
		24 AWG Stranded 600V	Teal TPE AWM CMX/CMR With Foil/Braided Shield -40°C to +80°C 7.6mm OD (0.30" OD)	≤ 86 Ω/Km	Yes	MDE45WB-8CBL-C	60GSW01-*

Ethernet Series

L

* Standard raw spool lengths are 0250, 0500, 0750 & 1000 feet. Consult factory for other lengths.

All testing is conducted off the reel and without connectors attached.

Cable Construction subject to change without notice.