



Foundation Fieldbus Series Cordsets

4 Conductor Foundation Fieldbus Cordsets, 18AWG



Straight Cordsets | 300 Volt, 10 amps | 300 Volt, 4 amps | IP69 Rating



Foundation Fieldbus Series

M

7/8"-16UN Cordsets					
Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	FFIN-4MPX-**-SS	Orange PVC ITC-ER With Foil Shield 2 X 18 AWG 300V, 10A -40°C to +105°C 7.2mm OD	Crush Proof Industry Standard PVC Stainless Steel Coupling Nut Foil Shield	1. Blue(-) 2. Orange(+) 3. Shield 4. N/C	<p>7/8"-16UN2</p>
	FFDC-4MPX-**-SS	Orange PVC ITC-ER With Foil Shield 2 X 18 AWG 1 x 22 AWG (Drain) 300V, 10A -40°C to +105°C 7.2mm OD	Crush Proof Industry Standard PVC Stainless Steel Coupling Nut Foil Shield	1. Blue(-) 2. Orange(+) 3. Shield 4. N/C	<p>7/8"-16UN2</p>
M12 Cordsets					
Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	FFIN-4FPX-**-SS	Orange PVC ITC-ER With Foil Shield 2 X 18 AWG 1 x 22 AWG (Drain) 300V, 4A -40°C to +105°C 7.2mm OD	Crush Proof Industry Standard PVC Stainless Steel Coupling Nut Foil Shield	1. Blue(-) 2. Orange(+) 3. Shield 4. N/C	<p>M12 x 1</p>
	FFDC-4FPX-**-SS	Orange PVC ITC-ER With Foil Shield 2 X 18 AWG 1 x 22 AWG (Drain) 300V, 4A -40°C to +105°C 7.2mm OD	Crush Proof Industry Standard PVC Stainless Steel Coupling Nut Foil Shield	1. Blue(-) 2. Orange(+) 3. Shield 4. N/C	<p>M12 x 1</p>

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.