



JDC (M12) Junction Blocks

12 Port, 5 Pin JDC Junction blocks



Cable | D-Sub | IP67 Protection Rating




Trunk Style	UL Rating	Trunk Connection	Part Number		
			No LED	PNP	NPN
	N/A	Black PUR AWM With Foil Shield 24 AWG Drain Wire 4 x 18 AWG 24 x 22 AWG 12.4mm OD	JDC-250-028-C**	JDC-25P-228-C**	JDC-25N-228-C**
	N/A	Gray PVC With Foil Shield 20 AWG Drain Wire 21 x 24 AWG 4 x 20 AWG	JDC-250-037-D**	JDC-25P-237-D**	JDC-25N-237-D**

** Lengths in meters. Standard cable lengths are 5m and 10m. Consult factory for other lengths.

JDC Junction Blocks

Q



Specifications:

Ratings:	3 A per Connector 8 A per Block	Inserts:	Polyamide
Voltage:	Without LEDs: 0-150 Volt Max With LEDs: 48 VDC Max in accordance with LED Configuration	Port Coupling Nuts:	Nickel Plated Brass
Body:	Polypropylene	O-Ring:	BUNA-N
		LED Lens:	Polycarbonate
		Contacts:	Copper Alloy with Gold Plating
		Marker Tags:	Polyamide (supplied on all units)