



WIRING		
COLOR	FUNCTION	MCV PIN
J1 - +	V+ (ALL PORTS PIN 1)	11
J1 - -	V- (ALL PORTS PIN 3)	9 & 10
J1 - GND	GND (ALL PORTS PIN 5)	12
J2 - 1	PORT 1 PIN 4	1
J2 - 2	PORT 2 PIN 4	2
J2 - 3	PORT 3 PIN 4	3
J2 - 4	PORT 4 PIN 4	4

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	REDRAWN IN SW	2/20/2007	



THIS IS A PNP BLOCK



MATERIALS:	
BODY:	PBT
MARKERS:	POLYAMIDE
INSERTS:	POLYAMIDE
MCV BODY:	NICKEL PLATED BRASS
CONTACTS:	GOLD PLATED COPPER ALLOY
O-RINGS:	NBR
RATINGS:	
VOLTS:	48VDC MAX
AMPS:	3A PER PORT, 10A PER BLOCK

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	MENCOM CORPORATION		
		DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	DWM	TITLE:		
			CHECKED				
			ENG APPR.				
			MFG APPR.				
			Q.A.		SIZE DWG. NO. REV		
			COMMENTS:				
		MATERIAL	B JDC-44P-212-V000 A				
		FINISH					
		DO NOT SCALE DRAWING	SCALE: 1:1		WEIGHT:	SHEET 1 OF 1	