




PANEL CUTOUT

$117.0^{+0.4}_{0.0}$
 $4.61^{+0.02}_{-0.00}$

2.0 MAX
 $R0.08 \text{ MAX}$

130.2
 5.13

CHINA OUTLET
CH1-10R
CCC RATING

(2X) RJ45 Cat 6 Jack
EXTERIOR/INTERIOR

3 POLE PLUGGABLE
TERMINAL BLOCK
FOR INCOMING POWER

116.9
 4.60

25
 1.0

(X4) USE PH2 SCREW
DRIVER ON MOUNTING
SCREWS. (REF. MOUNTING
SCREW TORQUE)

ROTATE TWO TURNS COUNTER
CLOCKWISE TO RELEASE THE
TURN BUCKLE PRIOR TO TIGHTENING

TURN BUCKLES ROTATE 90 DEG. INTO
THEIR CLAMPING POSITION AS
MOUNTING SCREWS TIGHTEN.
DO NOT OVER-TORQUE!

LOCK

DETAIL A
SCALE 1 : 1

SLIDE LATCH TO OPEN/CLOSE
ROTATE LOCK TO LOCK CLOSED

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS

VOLTS:	250V
AMPS:	10A
NEMA/UL EN 60529:	4, 12 IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

HOUSING MATERIALS	
BODY:	NICKEL PLATED ZINC
GASKETS:	PUR FIPG
FRONT COVER:	POLYCARBONATE
LATCH & LOCK:	PBT
BACK COVER:	POLYPROPYLENE

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

DRAWN BY	DCG
DRAWN DATE	09/24/2021
CHECKED BY	APR
CHECK DATE	09/24/2021

COMMENTS:

MENCOM CORPORATION

TITLE:

CHINA 10A RCPT; 2 RJ45; LP2

SIZE	DWG. NO.	REV
B	LP2-DCH1-2RJ45	A
SCALE: 1:2	WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

DO NOT SCALE DRAWING