



MCL (M16) Series Receptacles

12 & 14 Conductor MCL Series Receptacles, 24-28AWG




Front & Back Mount | Solder Cup | 60 Volt, 3 amps | Non-UL | IP67 Rating

E
M16 Series


Solder Cup : Front Mount Version					
# of Poles	Male Faceview	Rating	Wire AWG	Male Receptacles	Female Receptacles
12	 M16 x 1	60V 3A	24-28 AWG	MCL-12MR-M18-SC	MCL-12FR-M18-SC
14	 M16 x 1	60V 3A	24-28 AWG	MCL-14MR-M18-SC	MCL-14FR-M18-SC
Solder Cup : Back Mount Version					
12	 M16 x 1	60V 3A	24-28 AWG	MCL-12MR-M18-BM-SC	MCL-12FR-M18-BM-SC
14	 M16 x 1	60V 3A	24-28 AWG	MCL-14MR-M18-BM-SC	MCL-14FR-M18-BM-SC

Front Mount


Back Mount




Male Receptacle



Female Receptacle



Male Receptacle



Female Receptacle

Specifications:

- Shell: Nickel Plated Zinc Diecast
- Contacts: Copper Alloy with Gold Plating
- O-Ring: NBR
- Jam Nut: Nickel Plated Brass
- Insert: PBT
- Temperature: -30°C to +85°C (-22°F to +185°F)