


PIN #	COLOR
1	BROWN
2	BROWN / WHITE
3	BLUE
4	WHITE
5	GREEN
6	YELLOW
7	GRAY
8	PINK
9	RED
10	BLACK
11	VIOLET
12	GREEN / YELLOW





MATERIALS	
SHELL:	NICKEL PLATED BRASS
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1007/1569
AWG:	18 AWG
JACKET:	PVC
VOLTAGE:	300V
INSERT:	PBT
O-RING:	NBR
GASKET:	NBR
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES
RATINGS	
PROTECTION CLASS:	IEC IP69



Suggested Panel Cutout

PART NUMBER	L
MCV-12MR-0.3M-PM32	12" [0.3m]
MCV-12MR-0.5M-PM32	20" [0.5m]
MCV-12MR-0.6M-PM32	24" [0.6m]
MCV-12MR-1M-PM32	40" [1m]
MCV-12MR-2M-PM32	79" [2m]
MCV-12MR-3M-PM32	118" [3m]
MCV-12MR-5M-PM32	197" [5m]
MCV-12MR-10M-PM32	393" [10m]

OTHER LENGTHS ARE AVAILABLE
PLEASE CONSULT FACTORY

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	6A
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY	ADM
DRAWN DATE	08/30/2023
CHECKED BY	JJH
CHECK DATE	08/30/2023

COMMENTS:

MENCOM CORPORATION

TITLE:

SIZE	DWG. NO.	REV
B	MCV-12MR-ZZ-PM32	B

SCALE: 2:1 | WEIGHT: | SHEET 1 OF 1