



MCV (M23) Series Cordsets



12 Conductor M23 Series Cordsets, 18/22AWG



Straight Male Cordsets | 300 Volt, 6 & 2 amps | IP69 Rating



E
M23 Series

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MCVP-12MP-**	Black PUR AWM With Foil Shield 3 X 18 AWG 300V, 6A 9 X 22 AWG 300V, 2A -40°C to +80°C 8.1mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR Foil Shield	1. Brown*** 2. Brown/White 3. Blue*** 4. White 5. Green 6. Yellow 7. Gray 8. Pink 9. Red 10. Black 11. Violet 12. Green/Yellow***	 M23 x 1
	MCVW-12MP-**	Black TPE AWM With Foil Shield 3 X 18 AWG 300V, 6A 9 X 22 AWG 300V, 2A -40°C to +80°C 8.1mm OD	Weld Slag Resistant TPE Foil Shield		

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

*** Brown, Blue and Green/Yellow are 18AWG

Standard coupling nut is nickel plated brass. Stainless steel coupling nut is available only for female threads.

For stainless steel coupling nut add a “-SS” suffix. (e.g. MCVP-12MP-1M becomes MCVP-12MP-1M-SS)

Fixed Male Thread Option

For male threaded coupling replace “MP/MPX” with “MPM/MPMX”.

(e.g. MCVP-12MP-1M becomes MCVP-12MPM-1M)

