







MDC (M12) Series Receptacles

2, 3, 4 & 5 Conductor MDC Series Receptacles, 18/22AWG




Front Mount Receptacles | 1/4"-18 NPT Threads | 300 Volt, 4 amps | IP69 Rating




# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Nickel Plated Brass		Stainless Steel	
					Male Receptacles	Female Receptacles	Male Receptacles	Female Receptacles
2	 M12x1	3. Brown 4. Blue	300V 4A	18 AWG	MDC-2MR-4-18	MDC-2FR-4-18	MDC-2MR-4-18-SS	MDC-2FR-4-18-SS
				22 AWG	MDC-2MR-4	MDC-2FR-4	MDC-2MR-4-SS	MDC-2FR-4-SS
3	 M12x1	1. Brown 3. Blue 4. Black	300V 4A	18 AWG	MDC-3MR-4-18	MDC-3FR-4-18	MDC-3MR-4-18-SS	MDC-3FR-4-18-SS
				22 AWG	MDC-3MR-4	MDC-3FR-4	MDC-3MR-4-SS	MDC-3FR-4-SS
4	 M12x1	1. Brown 2. White 3. Blue 4. Black	300V 4A	18 AWG	MDC-4MR-4-18	MDC-4FR-4-18	MDC-4MR-4-18-SS	MDC-4FR-4-18-SS
				22 AWG	MDC-4MR-4	MDC-4FR-4	MDC-4MR-4-SS	MDC-4FR-4-SS
5	 M12x1	1. Brown 2. White 3. Blue 4. Black 5. Gray	300V 4A	18 AWG	MDC-5MR-4-18	MDC-5FR-4-18	MDC-5MR-4-18-SS	MDC-5FR-4-18-SS
				22 AWG	MDC-5MR-4	MDC-5FR-4	MDC-5MR-4-SS	MDC-5FR-4-SS

12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

1/4" NPT Nickel Plated Brass




Male Receptacles




Female Receptacles

1/4" NPT Stainless Steel



Male Receptacles



Female Receptacles

Specifications:

Shell: Nickel Plated Brass/Stainless Steel
Insulator: Polyamide
Wire: 18 & 22 AWG: 300V,
UL Style 1007/1569

Contacts: Copper Alloy with Gold Plating
Jam Nut: Nickel Plated Brass
O-Ring: NBR
Temperature: -40°C to 105°C (-40°F to +221°F)