PIN #	COLOR
1	BROWN
2	WHITE
3	BLUE
4	BLACK





MATERIALS	
SHELL:	STAINLESS STEEL
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1007/1569
AWG:	18 AWG
JACKET:	PVC
VOLTAGE:	300V
INSERT:	POLYAMIDE
O-RING:	NBR
NUT:	ZINC PLATED STEEL
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

TABLE A	
P/N	L
MDC-4MR-2-18-SS	12" [0.3m]
MDC-4MR-2-0.5M-18-SS	20" [0.5m]
MDC-4MR-2-0.6M-18-SS	24" [0.6M]
MDC-4MR-2-1M-18-SS	40" [1m]
MDC-4MR-2-2M-18-SS	79" [2m]
MDC-4MR-2-3M-18-SS	118" [3m]
MDC-4MR-2-5M-18-SS	197" [5m]
MDC-4MR-2-10M-18-SS	393" [10m]

OTHER LENGTHS AVAILABLE,
PLEASE CONSULT FACTORY

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	4A
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY	ADM
DRAWN DATE	07/18/2023
CHECKED BY	JJH
CHECK DATE	07/19/2023

COMMENTS:

MENCOM CORPORATION

TITLE:

4 PL SS ML RCPT 1/2"
18AWG

SIZE	DWG. NO.	REV
B	MDC-4MR-2-ZZ-18-SS	C

SCALE: 2:1 | WEIGHT: | SHEET 1 OF 1