

PIN #	COLOR
1	BROWN
2	WHITE
3	BLUE
4	BLACK
5	GRAY

MATERIALS	
SHELL:	STAINLESS STEEL
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1007/1569
AWG:	18/5
JACKET:	PVC
VOLTAGE:	300V
INSERT:	POLYAMIDE
O-RING:	NBR & FPM
NUT:	ZINC PLATED STEEL
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

TABLE A	
P/N	L
MDC-5FR-4-0.15M-18-SS	6" [0.15M]
MDC-5FR-4-18-SS	12" [0.3M]
MDC-5FR-4-0.5M-18-SS	20" [0.5M]
MDC-5FR-4-0.6M-18-SS	24" [0.6M]
MDC-5FR-4-1M-18-SS	40" [1M]
MDC-5FR-4-2M-18-SS	79" [2M]
MDC-5FR-4-5M-18-SS	197" [5M]
MDC-5FR-4-10M-18-SS	393" [10M]

OTHER LENGTHS AVAILABLE
PLEASE CONSULT FACTORY

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS

AMPS

TEMP:

300V

4A

105°C

DRAWN BY

DRAWN DATE

CHECKED BY

CHECK DATE

COMMENTS:

ADM

11/10/2021

JJH

11/10/2021

TITLE:

SIZE

DWG. NO.

REV

5 POL FEM RECP 1/4" NPT S.S.

B

MDC-5FR-4-ZZ-18-SS

B

SCALE: 2:1

WEIGHT:

SHEET 1 OF 1