











DeviceNet Series Cordsets

5 Conductor DeviceNet Series Cordsets, 15/18AWG & 22/24AWG



Straight Male Cordsets | 600 Volt, 8 amps | 300 Volt, 4 amps | IP69/IP67 Rating



7/8"-16UN Trunk Cordsets - Thick Cable					
Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
 7/8-16UN2A	MINDT-5MP-**	Gray PVC Trunk Cable AWM With Braided Shield 2 X 15 AWG 2 X 18 AWG 1 x 18 AWG (Drain) 600V, 8A -40°C to +80°C 11.2mm OD	Industry Standard PVC Braided Shield IP69	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	 7/8"-16UN2
7/8"-16UN & M12 Drop Cordsets - Thin Cable					
 7/8-16UN2A	MINDD-5MP-**	Gray PVC Drop Cable AWM With Braided Shield 2 X 22 AWG 2 X 24 AWG 1 x 22 AWG (Drain) 300V, 4A -40°C to +80°C 7.4mm OD	Industry Standard PVC Braided Shield IP69	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	 7/8"-16UN2
 M12x1	MDCDD-5MP-**	Gray PVC Drop Cable AWM With Braided Shield 2 X 22 AWG 2 X 24 AWG 1 x 22 AWG (Drain) 300V, 4A -40°C to +80°C 7.4mm OD	Industry Standard PVC Braided Shield IP69	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	 M12 x 1
 M12x1	MDCUT-5MP-**	Gray PVC Drop Cable AWM With Foil Shield 2 X 24 AWG 2 X 24 AWG 1 x 24 AWG (Drain) 300V, 3A -40°C to +80°C 5.7mm OD	Industry Standard PVC Foil Shield IP67	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	 M12 x 1

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MINDD-5MP-1M becomes MINDD-5MP-1M-SS)