





# Ethernet (M12) Series Etherplug Cordsets

4 Conductor Ethernet Series Cordsets, 24AWG



Right Angle Male Cordsets | 300 Volt, 4 amps | CAT5e | D-Coded | Twisted Pairs | IP69 Rating



| Connector Body Style                                                               | Part Number                                                | Cables                                                                                                       | Features                                                                                               | Color Code                                                 | Faceview                                                                                       |
|------------------------------------------------------------------------------------|------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------------------------------------------|
|  | MDE45-4MP-**-R                                             | Teal PVC<br>AWM<br><b>4 X 24 AWG</b><br>300V, 4A<br>-20°C to +80°C<br>6.1mm OD                               | Industry Standard PVC                                                                                  | 1. White/Orange<br>2. White/Green<br>3. Orange<br>4. Green | <br>M12 x 1 |
|                                                                                    | MDE45B-4MP-**-R                                            | Teal PVC<br>AWM<br>With Foil & Braided Shield<br><b>4 X 26 AWG</b><br>300V, 4A<br>-20°C to +80°C<br>6.6mm OD | Industry Standard PVC<br>Foil & Braided Shield                                                         |                                                            |                                                                                                |
|                                                                                    | MDE45P-4MP-**-R                                            | Teal PUR<br>AWM<br><b>4 X 24 AWG</b><br>300V, 4A<br>-40°C to +80°C<br>5.6mm OD                               | Continuous-Flex<br>Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR                          |                                                            |                                                                                                |
|                                                                                    | MDE45PB-4MP-**-R                                           | Teal PUR<br>AWM<br>With Foil & Braided Shield<br><b>4 X 24 AWG</b><br>300V, 4A<br>-40°C to +80°C<br>6.4mm OD | Continuous-Flex<br>Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR<br>Foil & Braided Shield |                                                            |                                                                                                |
|                                                                                    | MDE45WB-4MP-**-R<br>(Teal)<br>MDE45WB-4MP-**-R-RD<br>(Red) | TPE<br>AWM<br>With Foil & Braided Shield<br><b>4 X 24 AWG</b><br>300V, 4A<br>-40°C to +80°C<br>6.6mm OD      | Continuous-Flex<br>Weld Slag<br>Resistant TPE<br>Foil & Braided Shield                                 |                                                            |                                                                                                |

\*\* Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MDE45-4MP-1M-R becomes MDE45-4MP-1M-R-SS)