















MDC (M12) to NAN (M8) Cordsets

3 & 4 Conductor MDC Series Cordsets, 24AWG




Double Ended Cordsets | 60 Volt, 4 amps | IP67 Rating




Male MDC to Threaded Female NAN					
Male Faceview	Part Number	Cables	Features	Wiring	Female Faceview
 M12 x 1	MDNT-3MFP-**	Black PVC AWM 3 X 24 AWG 60V, 3A -40°C to +105°C 4.5mm OD	Industry Standard PVC	1 to 1 3 to 3 4 to 4	 M8 x 1
 M12 x 1	MDNT-4MFP-**	Black PVC AWM 4 X 24 AWG 60V, 3A -40°C to +80°C 4.5mm OD	Industry Standard PVC	1 to 1 2 to 2 3 to 3 4 to 4	 M8 x 1
Threaded Male NAN to Female MDC					
 M8 x 1	NANTDC-3MFP-**	Black PVC AWM 3 X 24 AWG 60V, 3A -40°C to +105°C 4.5mm OD	Industry Standard PVC	1 to 1 3 to 3 4 to 4	 M12 x 1
 M8 x 1	NANTDC-4MFP-**	Black PVC AWM 4 X 24 AWG 60V, 3A -40°C to +80°C 4.5mm OD	Industry Standard PVC	1 to 1 2 to 2 3 to 3 4 to 4	 M12 x 1
Snap-On Male NAN to Female MDC					
 M8 x 1	NANDC-3MFP-**	Black PVC AWM 3 X 24 AWG 60V, 3A -40°C to +105°C 4.5mm OD	Industry Standard PVC	1 to 1 3 to 3 4 to 4	 M12 x 1
 M8 x 1	NANDC-4MFP-**	Black PVC AWM 4 X 24 AWG 60V, 3A -40°C to +80°C 4.5mm OD	Industry Standard PVC	1 to 1 2 to 2 3 to 3 4 to 4	 M12 x 1

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a “-SS” suffix. (e.g. NANDC-4MFP-1M becomes NANDC-4MFP-1M-SS)



Male MDC to Threaded Female NAN Extension



Threaded Male NAN to Female MDC Extension



Snap-On Male NAN to Female MDC Extension