



# 1 1/8" MIN Series Size III Cordsets

9 & 10 Conductor MIN Series Size III Cordsets, 16/18AWG



Right Angle Male Cordsets | 600V, 7A | 300V, 4A | IP69 Rating



C

MIN Series Size III Cordsets

| Connector Body Style | Part Number      | Cables                                                                       | Features                                                   | Color Code                                                                                                                                                                 | Faceview         |
|----------------------|------------------|------------------------------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
|                      | MIN-9MP-*R-C011  | Black PVC<br>AWM<br>9 X 16 AWG<br>600V, 7A<br>-40°C to +105°C<br>12.1mm OD   | PVC<br>TC-ER                                               | <b>North American</b><br>1. Orange<br>2. Blue<br>3. Red/Black<br>4. Green/Black<br>5. White<br>6. Red<br>7. Green/Yellow<br>8. White/Black<br>9. Black                     | <br>1 1/8"-16UN2 |
|                      | MIN-9MPX-*R      | Yellow PVC<br>AWM<br>9 X 18 AWG<br>300V, 4A<br>-40°C to +105°C<br>9.2mm OD   | Industry Standard PVC                                      |                                                                                                                                                                            |                  |
|                      | MINP-9MPX-*R     | Yellow PUR<br>AWM<br>9 X 18 AWG<br>300V, 4A<br>-40°C to +80°C<br>9.2mm OD    | Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR | <b>North American</b><br>1. Orange<br>2. Blue<br>3. Red/Black<br>4. Green/Black<br>5. White<br>6. Red<br>7. Green/Yellow<br>8. White/Black<br>9. Black                     | <br>1 1/8"-16UN2 |
|                      | MIN-10MP-*R-C011 | Black PVC<br>AWM<br>10 X 16 AWG<br>600V, 7A<br>-40°C to +105°C<br>14mm OD    | PVC<br>TC-ER                                               |                                                                                                                                                                            |                  |
|                      | MIN-10MPX-*R     | Yellow PVC<br>AWM<br>10 X 18 AWG<br>300V, 4A<br>-40°C to +105°C<br>10.1mm OD | Industry Standard PVC                                      | <b>North American</b><br>1. Orange<br>2. Blue<br>3. White/Black<br>4. Red/Black<br>5. Green/Black<br>6. Orange/Black<br>7. Red<br>8. Green/Yellow<br>9. Black<br>10. White | <br>1 1/8"-16UN2 |
|                      | MINP-10MPX-*R    | Yellow PUR<br>AWM<br>10 X 18 AWG<br>300V, 4A<br>-40°C to +80°C<br>10.1mm OD  | Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR |                                                                                                                                                                            |                  |

\* Length in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MIN-10MPX-3-R becomes MIN-10MPX-3-R-SS)

For male threaded coupling nut replace "MPX" with "MPMX". (e.g. MIN-10MPX-3-R becomes MIN-10MPMX-3-R)