

8 7 6 5 4 3 2 1

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/1/2005	

PIN #	COLOR
1	ORANGE
2	BLUE
3	WHITE w/BLACK
4	RED w/BLACK
5	GREEN w/BLACK
6	ORANGE w/BLACK
7	BLUE w/BLACK
8	BLACK w/WHITE
9	GREEN / YELLOW
10	RED
11	WHITE
12	BLACK

1.125"-16 UN

M25x1.5

L

29.1
1.15

7.3
.29

P/N	L	STD?
MIN-12MR-.5-22-M25	6.5"	NO
MIN-12MR-1-22-M25	12.5"	YES
MIN-12MR-2-22-M25	24"	NO
MIN-12MR-3-22-M25	36"	YES
MIN-12MR-4-22-M25	48"	NO
MIN-12MR-5-22-M25	60"	NO
MIN-12MR-6-22-M25	72"	YES
MIN-12MR-10-22-M25	120"	NO
MIN-12MR-15-22-M25	180"	NO
MIN-12MR-20-22-M25	240"	NO

PARTS LISTED AS NOT BEING STANDARD
MAY HAVE MINIMUM ORDER QUANTITIES

MATERIALS:	
BODY:	CLEAR ANODIZED ALUMINUM
INSERT:	YELLOW PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRE:	22AWG UL1007
O-RING:	BUNA-N

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

SPECIFICATIONS	
VOLTS	300V
AMPS	4A
TEMP	105°C

MENCOM CORPORATION			
TITLE:			
SIZE	DWG. NO.	REV	
B	MIN-12MR-ZZ-22-M25	A	
SCALE: 2:1		WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

8 7 6 5 4 3 2 1