



1 1/8" MIN Series Size III Cordsets

12 Conductor MIN Series Size III Cordsets, 16/18AWG






Right Angle Male Cordsets | 600V, 5A | 300V, 4A | IP69 Rating



C

MIN Series Size III Cordsets

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MIN-12MPX-*R-C011	Black PVC AWM 12 X 16 AWG 600V, 5A -40°C to +105°C 14mm OD	PVC TC-ER	North American 1. Orange 2. Blue 3. White/Black 4. Red/Black 5. Green/Black 6. Orange/Black 7. Blue/Black 8. Black/White 9. Green/Yellow 10. Red 11. White 12. Black	 1 1/8"-16UN2
	MIN-12MPX-*R	Yellow PVC AWM 12 X 16 AWG 300V, 4A -40°C to +105°C 10.5mm OD	Industry Standard PVC		
	MINP-12MPX-*R	Yellow PUR AWM 12 X 18 AWG 300V, 4A -40°C to +80°C 10.5mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		

* Length in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MIN-10MPX-3-R becomes MIN-10MPX-3-R-SS)

For male threaded coupling nut replace "MPX" with "MPMX". (e.g. MIN-12MPX-3-R becomes MIN-12MPMX-3-R)