

PIN #	COLOR
1	VIOLET
2	RED
3	GRAY
4	RED w/BLUE
5	BLUE
6	GREEN
7	BROWN
8	WHITE w/GREEN
9	WHITE w/YELLOW
10	WHITE w/GRAY
11	BLACK
12	GREEN / YELLOW
13	YELLOW w/BROWN
14	BROWN w/GREEN
15	WHITE
16	YELLOW
17	PINK
18	GRAY w/BROWN
19	GRAY w/PINK

MATERIALS:	
SHELL:	CLEAR ANODIZED ALUMINUM
INSERT:	YELLOW PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRE:	18 & 22AWG UL1007/1569
O-RING:	NBR
LOCKNUT	ZINC PLATED STEEL
APPROVALS	
U.S.	UL LISTED
CANADA	C-UL LISTED

PINS 5, 7 & 12 ARE 18AWG

1.125"-16UN2A

1/2-14 NPT

L

29
1.1

11
.4

32
1.3

Please note that to better serve the varying needs of our customers, these parts have been UL tested for two different amperage ratings as shown by our Ratings table.

RATINGS:	
PIN 12	GROUND
PINS 5 & 7	300V, 6A
ALL OTHERS	300V, 1A
OR	
PIN 12	GROUND
PINS 5 & 7	300V, 4A
ALL OTHERS	300V, 2A

VOLTS		300V
AMPS	6A/1A OR 4A/2A	
TEMP:	105°C	

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

MENCOM CORPORATION		
TITLE:		
19 PL MIN ML RECP		
SIZE	DWG. NO.	REV
B	MIN-19MR-ZZ	B
SCALE: 3:2	WEIGHT:	SHEET 1 OF 1