



# 7/8" MIN Series Size I Receptacles

2, 3, 4, 5 & 6 Conductor MIN Series Size I Receptacles, 16/18/22AWG



Panel Mount Receptacles | IP69 Rating



A

MIN Series Size I Receptacles

# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles
2	<p>7/8"-16UN2</p>	<b>North American</b> 1. White 2. Black	600V 13A	16 AWG	MIN-2MR-1-PM	MIN-2FR-1-PM
			300V 10A	18 AWG	MIN-2MR-1-18-PM	MIN-2FR-1-18-PM
			300V 4A	22 AWG	MIN-2MR-5-22-PM	MIN-2FR-1-22-PM
3	<p>7/8"-16UN2</p>	<b>North American</b> 1. Green/Yellow 2. Black 3. White	600V 13A	16 AWG	MIN-3MR-1-PM	MIN-3FR-1-PM
			300V 10A	18 AWG	MIN-3MR-1-18-PM	MIN-3FR-1-18-PM
			300V 4A	22 AWG	MIN-3MR-5-22-PM	MIN-3FR-1-22-PM
4	<p>7/8"-16UN2</p>	<b>North American</b> 1. Black 2. White 3. Red 4. Green/Yellow	600V 10A	16 AWG	MIN-4MR-1-PM	MIN-4FR-1-PM
			300V 5.5A	18 AWG	MIN-4MR-1-18-PM	MIN-4FR-1-18-PM
			300V 4A	22 AWG	MIN-4MR-5-22-PM	MIN-4FR-1-22-PM
5	<p>7/8"-16UN2</p>	<b>North American</b> 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black	600V 8A	16 AWG	MIN-5MR-1-PM	MIN-5FR-1-PM
			300V 5.5A	18 AWG	MIN-5MR-1-18-PM	MIN-5FR-1-18-PM
			300V 4A	22 AWG	MIN-5MR-5-22-PM	MIN-5FR-1-22-PM
6	<p>7/8"-16UN2</p>	<b>North American</b> 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black 6. Blue	600V 8A	16 AWG	MIN-6MR-1-PM	MIN-6FR-1-PM
			300V 5.5A	18 AWG	MIN-6MR-1-18-PM	MIN-6FR-1-18-PM
			300V 4A	22 AWG	MIN-6MR-5-22-PM	MIN-6FR-1-22-PM

12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

Flat gasket is included.

### Specifications:

- Shell: Blue Anodized Aluminum
- Insulator: 105°C, Oil Resistant Yellow PVC
- Wire: 16 AWG: UL Style 1015, 600V  
18 & 22 AWG: UL Style 1007/1569, 300V
- Contacts: Copper Alloy with Gold Plating
- Gasket: NBR
- Temperature: -40°C to 105°C (-40°F to +221°F)

