



7/8" MIN Series Size I Receptacles

2, 3, 4, 5 & 6 Conductor MIN Series Size I Receptacles, 16/18/22AWG








Right Angle Front Mount Receptacles | 1/2"-14 NPT Threads | IP69 Rating



A

MIN Series Size I Receptacles

# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles
2	 7/8"-16UN2	North American 1. White 2. Black	600V 13A	16 AWG	MIN-2MR-1-R	MIN-2FR-1-R
			300V 10A	18 AWG	MIN-2MR-1-18-R	MIN-2FR-1-18-R
			300V 4A	22 AWG	MIN-2MR-1-22-R	MIN-2FR-1-22-R
3	 7/8"-16UN2	North American 1. Green/Yellow 2. Black 3. White	600V 13A	16 AWG	MIN-3MR-1-R	MIN-3FR-1-R
			300V 10A	18 AWG	MIN-3MR-1-18-R	MIN-3FR-1-18-R
			300V 4A	22 AWG	MIN-3MR-1-22-R	MIN-3FR-1-22-R
4	 7/8"-16UN2	North American 1. Black 2. White 3. Red 4. Green/Yellow	600V 10A	16 AWG	MIN-4MR-1-R	MIN-4FR-1-R
			300V 5.5A	18 AWG	MIN-4MR-1-18-R	MIN-4FR-1-18-R
			300V 4A	22 AWG	MIN-4MR-1-22-R	MIN-4FR-1-22-R
5	 7/8"-16UN2	North American 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black	600V 8A	16 AWG	MIN-5MR-1-R	MIN-5FR-1-R
			300V 5.5A	18 AWG	MIN-5MR-1-18-R	MIN-5FR-1-18-R
			300V 4A	22 AWG	MIN-5MR-1-22-R	MIN-5FR-1-22-R
6	 7/8"-16UN2	North American 1. White 2. Red 3. Green/Yellow 4. Orange 5. Black 6. Blue	600V 8A	16 AWG	MIN-6MR-1-R	MIN-6FR-1-R
			300V 5.5A	18 AWG	MIN-6MR-1-18-R	MIN-6FR-1-18-R
			300V 4A	22 AWG	MIN-6MR-1-22-R	MIN-6FR-1-22-R

10" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

Specifications:

Shell:	Hex: Clear Anodized Aluminum Elbow: Zinc Die Cast
Insulator:	105°C, Oil Resistant Yellow PVC
Wire:	16 AWG: UL Style 1015, 600V 18 & 22 AWG: UL Style 1007/1569, 300V
Contacts:	Copper Alloy with Gold Plating
O-Ring:	NBR
Lock Nut:	Zinc Plated Steel
Temperature:	-40°C to 105°C (-40°F to +221°F)

