



# 7/8" MIN Series Size I Cordsets

2 & 3 Conductor MIN Series Size I Cordsets, 16AWG



Straight Male Cordsets | 600 Volt, 13 amps | IP69 Rating

A

MIN Series Size I Cordsets



Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MIN-2MP-*	Yellow PVC STOOW <b>2 X 16 AWG</b> 600V, 13A -40°C to +105°C 9.4mm OD	Industry Standard PVC	<b>North American</b> 1. White 2. Black	 7/8"-16UN2
	MIN-3MP-*(YELLOW) MIN-3MP-*(BLACK)	PVC STOOW <b>3 X 16 AWG</b> 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC	<b>North American</b> 1. Green/Yellow 2. Black 3. White	 7/8"-16UN2
	MINM-3MP-*	Yellow PVC STOOW With Foil Shield <b>3 X 16 AWG</b> 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC Foil Shield	<b>North American</b> 1. Green/Yellow 2. Black 3. White	 7/8"-16UN2
	MINP-3MP-*	Yellow PUR AWM <b>3 X 16 AWG</b> 600V, 13A -40°C to +80°C 10mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MINW-3MP-*(YELLOW) MINW-3MP-*(BLACK)	TPE SEOOW <b>3 X 16 AWG</b> 600V, 13A -40°C to +80°C 10mm OD	Weld Slag Resistant TPE		
	MIN-3MP-*A	Yellow PVC STOOW <b>3 X 16 AWG</b> 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC	<b>North American Auto Color Code</b> 1. Green/Yellow 2. Red/Black 3. Red/White	 7/8"-16UN2

\* Lengths in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MIN-3MP-3 becomes MIN-3MP-3-SS)

See Page A-33 for Armored Cordset options.

### Male Thread Option

For male threaded coupling replace "MP" with "MPM".

(e.g. MIN-3MP-3 becomes MIN-3MPM-3)

