

PIN #	COLOR	PIN #	COLOR
1	VIOLET	11	BLACK
2	RED	12	GRN / YEL
3	GRAY	13	YELLOW w/BRWN
4	RED w/BLUE	14	BROWN w/GRN
5	BLUE	15	WHITE
6	GREEN	16	YELLOW
7	BROWN	17	PINK
8	WHITE w/GRN	18	GRAY w/BRWN
9	WHITE w/YEL	19	GRAY w/PINK
10	WHITE w/GRY		

PINS 5, 7 & 12 ARE 18AWG

MATERIALS	
BODY:	CLEAR ANODIZED ALUMINUM
INSERT:	YELLOW PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	18AWG & 22AWG UL1007/1569
O-RING:	NBR
LOCK-NUT:	NICKEL PLATED BRASS

APPROVALS	
U.S.	UL LISTED
CANADA	C-UL LISTED

Please note that to better serve the varying needs of our customers, these parts have been UL tested for two different amperage ratings as shown by our Ratings table.

RATINGS:	
PIN 12	GROUND
PINS 5 & 7	300V, 6A
ALL OTHERS	300V, 1A
OR	
PIN 12	GROUND
PINS 5 & 7	300V, 4A
ALL OTHERS	300V, 2A

VOLTS		300V
AMPS	6A/1A OR 4A/2A	
TEMP:	105°C	

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

TABLE A			
P/N	L		
MIN-19MR-0.3M-PG16	12" [0.3m]		
MIN-19MR-0.5M-PG16	20" [0.5m]		
MIN-19MR-0.6M-PG16	24" [0.6m]		
MIN-19MR-1M-PG16	40" [1m]		
MIN-19MR-2M-PG16	79" [2m]		
MIN-19MR-3M-PG16	118" [3m]		
MIN-19MR-5M-PG16	197" [5m]		
MIN-19MR-10M-PG16	393" [10m]		

MENCOM CORPORATION			
TITLE:			
19 POL MAL RECP w/PG16 THRDS			
SIZE	DWG. NO.	REV	
B	MIN-19MR-ZZ-PG16	A	
SCALE: 1.5:1		WEIGHT:	SHEET 1 OF 1