



# 7/8" MIN Series Size I Cordsets

4 Conductor MIN Series Size I Cordsets, 18AWG







Straight Female Cordsets | 300 Volt, 5.5 amps | IP69 Rating



A

MIN Series Size I Cordsets

| Connector Body Style                                                                           | Part Number   | Cables                                                                              | Features                                                   | Color Code                                                                 | Faceview                                                                                           |
|------------------------------------------------------------------------------------------------|---------------|-------------------------------------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
|   | MIN-4FPX-*    | Yellow PVC<br>AWM<br><b>4 X 18 AWG</b><br>300V, 5.5A<br>-40°C to +105°C<br>7.4mm OD | Industry Standard PVC                                      | <b>North American</b><br>1. Black<br>2. White<br>3. Red<br>4. Green/Yellow | <br>7/8"-16UN2  |
|  | MINC-4FPX-**  | Yellow PVC<br>AWM<br><b>4 X 18 AWG</b><br>300V, 5.5A<br>-40°C to +105°C<br>7.4mm OD | Industry Standard PVC                                      | <b>European Cenelec</b><br>1. Brown<br>2. White<br>3. Blue<br>4. Black     | <br>7/8"-16UN2 |
|                                                                                                | MINCP-4FPX-** | Yellow PUR<br>AWM<br><b>4 X 18 AWG</b><br>300V, 5.5A<br>-40°C to +80°C<br>7.4mm OD  | Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR |                                                                            |                                                                                                    |
|                                                                                                | MINCW-4FPX-** | Yellow TPE<br>AWM<br><b>4 X 18 AWG</b><br>300V, 5.5A<br>-40°C to +80°C<br>7.4mm OD  | Weld Slag<br>Resistant TPE                                 |                                                                            |                                                                                                    |

\* Lengths in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

\*\* Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MIN-4FPX-3 becomes MIN-4FPX-3-SS)

See Page A-33 for Armored Cordset options.