

PIN #	COLOR
1	WHITE
2	RED
3	GREEN/YELLOW
4	ORANGE
5	BLACK

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	REDRAWN IN SW	12/14/2004	

D

C

B

A

MATERIALS	
BODY:	CLEAR ANODIZED ALUMINUM
CONTACTS:	GOLD PLATED COPPER ALLOY
INSERT:	YELLOW PVC
WIRE:	18AWG UL1007
O-RING:	NBR

CERTIFICATIONS	
U.S.	UL LISTED
CANADA	C-UL LISTED

7/8-16UN2A

M20x1.5

[17]
.67

[6.1]
.24

L

[25.4]
1.0

TABLE A

P/N

L

MIN-5MR-1-18-M20

12" [0.3m]

MIN-5MR-2-18-M20

24" [0.6m]

MIN-5MR-3-18-M20

36" [0.9m]

MIN-5MR-4-18-M20

48" [1.2m]

MIN-5MR-6-18-M20

72" [1.8m]

MIN-5MR-10-18-M20

120" [3.1m]

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

NAME

DRAWN

BEM

CHECKED

ENG APPR.

MFG APPR.

Q.A.

COMMENTS:

MENCOM CORPORATION

TITLE:

5 POL MAL RECP

SIZE

B

DWG. NO.

MIN-5MR-ZZ-18-M20

REV

A

SCALE: 2:1

WEIGHT:

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

VOLTS

300V

AMPS

5.5A

TEMP

105°C

SPECIFICATIONS