

PIN #	COLOR
1	WHITE
2	RED
3	GREEN / YELLOW
4	ORANGE
5	BLACK

MATERIALS:	
BODY:	CLEAR ANODIZED ALUMINUM
CONTACTS:	GOLD PLATED COPPER ALLOY
INSERT:	YELLOW PVC
WIRE:	18AWG UL1007/1569
O-RING:	BUNA-N
LOCKNUT:	ZINC PLATED STEEL

CERTIFICATIONS	
U.S.	UL LISTED
CANADA	C-UL LISTED

FOR LENGTHS OF 24" AND LONGER, AN O-RING AND LOCKNUT ARE INCLUDED

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	REDRAWN IN SW	5/20/2005	
B	UPDATED TO SHOW 1569 RATING ON WIRE	11/6/2009	

TABLE A	
P/N	L
MIN-5MR-1-18	12" [0.3m]
MIN-5MR-2-18	24" [0.6m]
MIN-5MR-3-18	36" [0.9m]
MIN-5MR-4-18	48" [1.2m]
MIN-5MR-5-18	60" [1.5m]
MIN-5MR-6-18	72" [1.8m]
MIN-5MR-8-18	96" [2.4m]
MIN-5MR-10-18	120" [3.0m]
MIN-5MR-15-18	180" [4.6m]
MIN-5MR-20-18	240" [6.1m]

UNLESS OTHERWISE SPECIFIED:		NAME
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	BEM
	CHECKED	
	ENG APPR.	
	MFG APPR.	
	Q.A.	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.	VOLTS	300V
	AMPS	5.5A
	TEMP	105°C
	SPECIFICATIONS	

MENCOM CORPORATION		
TITLE:		
5 POL MALE RECP 18AWG		
SIZE	DWG. NO.	REV
B	MIN-5MR-ZZ-18	B
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1