



1" MIN Series Size II Cordsets




8 Conductor MIN Series Size II Cordsets, 16/18AWG



Straight Male Cordsets | 600V, 7A | 300V, 5A | IP69 Rating



B
MIN Series Size II Cordsets

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MIN-8MP-*C011	Black PVC AWM 8 X 16 AWG 600V, 7A -40°C to +105°C 11.6mm OD	PVC TC-ER	North American 1. Orange 2. Blue 3. White/Black 4. Black 5. White 6. Red 7. Green/Yellow 8. Red/Black	 1"-16UN2
	MIN-8MPX-* (Yellow) MIN-8MPX-*B (Black)	PVC AWM 8 X 18 AWG 300V, 5A -40°C to +105°C 9.1mm OD	Industry Standard PVC		
	MINP-8MPX-*	Yellow PUR AWM 8 X 18 AWG 300V, 5A -40°C to +80°C 9.1mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		

* Length in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MIN-8MPX-3 becomes MIN-8MPX-3-SS)

For male threaded coupling replace "MP" with "MPM". (e.g. MIN-8MPX-3 becomes MIN-8MPMX-3)