



# DeviceNet Series Cordsets


## 5 Conductor DeviceNet Series Cordsets, 15/18AWG



Double Ended Cordsets | 600 Volt, 8 amps | 300 Volt, 4 amps | IP69 Rating



| 7/8"-16UN Trunk Extension - Thick Cable |                |                                                                                                                                                                      |                                                                   |                                                                                        |                 |
|-----------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------------------------------------------------------------|-----------------|
| Male Faceview                           | Part Number    | Cables                                                                                                                                                               | Features                                                          | Color Code                                                                             | Female Faceview |
| <br>7/8"-16UN2                          | MINDT-5MFP-**- | Gray PVC Trunk Cable<br>AWM<br>With Braided Shield<br><b>2 X 15 AWG</b><br><b>2 X 18 AWG</b><br><b>1 x 18 AWG (Drain)</b><br>600V, 8A<br>-40°C to +80°C<br>11.2mm OD | Industry Standard PVC<br>7/8"-16UN to 7/8"-16UN<br>Braided Shield | 1. Bare (Drain)<br>2. Red (V+)<br>3. Black (V-)<br>4. White (CAN_H)<br>5. Blue (CAN_L) | <br>7/8"-16UN2  |
| 7/8"-16UN Drop Extension - Thin Cable   |                |                                                                                                                                                                      |                                                                   |                                                                                        |                 |
| <br>7/8"-16UN2                          | MINDD-5MFP-**- | Gray PVC Drop Cable<br>AWM<br>With Braided Shield<br><b>2 X 22 AWG</b><br><b>2 X 24 AWG</b><br><b>1 x 22 AWG (Drain)</b><br>300V, 4A<br>-40°C to +80°C<br>7.4mm OD   | Industry Standard PVC<br>7/8"-16UN to 7/8"-16UN<br>Braided Shield | 1. Bare (Drain)<br>2. Red (V+)<br>3. Black (V-)<br>4. White (CAN_H)<br>5. Blue (CAN_L) | <br>7/8"-16UN2  |




Male(Male Thread) 7/8"-16UN to Female 7/8"-16UN Extension

| 7/8"-16UN Male to M12 Female Extension - Thin Cable |                  |                                                                                                                                                                    |                                                             |                                                                                        |                 |
|-----------------------------------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------------------------------------|-----------------|
| Male Faceview                                       | Part Number      | Cables                                                                                                                                                             | Features                                                    | Color Code                                                                             | Female Faceview |
| <br>7/8"-16UN2                                      | MINDCDD-5MFP-**- | Gray PVC Drop Cable<br>AWM<br>With Braided Shield<br><b>2 X 22 AWG</b><br><b>2 X 24 AWG</b><br><b>1 x 22 AWG (Drain)</b><br>300V, 4A<br>-40°C to +80°C<br>7.4mm OD | Industry Standard PVC<br>7/8"-16UN to M12<br>Braided Shield | 1. Bare (Drain)<br>2. Red (V+)<br>3. Black (V-)<br>4. White (CAN_H)<br>5. Blue (CAN_L) | <br>M12 x 1     |

\*\* Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MINDCDD-5MFP-1M becomes MINDCDD-5MFP-1M-SS)



Male 7/8"-16UN to Female M12 Extension