



MIL-SPEC Series Cordsets

2 & 3 Conductor 5015 Industrial Equiv. Cordsets, 16AWG



Straight Male Cordsets | Size 16S | 600 Volt, 13 amps | IP67 Rating



F
MIL-SPEC

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MS16S-2MP-**-	Yellow PVC STOOW 2 X 16 AWG 600V, 13A -40°C to 105°C 9.5mm OD	Industry Standard PVC	North American A. White B. Black	 16S-2 1.000"-20UNEF
	MS16S-3AMP-**- MS16S-3BMP-**- (YELLOW) MS16S-3AMP-**-B MS16S-3BMP-**-B (BLACK)	PVC STOOW 3 X 16 AWG 600V, 13A -40°C to 105°C 10mm OD	Industry Standard PVC	North American A. Green/Yellow B. Black C. White	 16S-3A 1.000"-20UNEF
	MS16SP-3AMP-**- MS16SP-3BMP-**-	Yellow PUR AWM 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		 16S-3B 1.000"-20UNEF
	MS16SW-3AMP-**- MS16SW-3BMP-**- (YELLOW) MS16SW-3AMP-**-B MS16SW-3BMP-**-B (BLACK)	TPE SEOOW 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Weld Slag Resistant TPE		

** Lengths in meters. Standard Cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated aluminum, for black anodized aluminum coupling nut add a "-BA" suffix. (e.g. MS16S-3MP-1M becomes MS16S-3MP-1M-BA)

Insert clocking, where available, is indicated by placing 'A or B' after the pin count in the part number. (e.g. MS16S-3MP-**- becomes MS16S-3AMP-**-)