







MIL-SPEC Series Receptacles

3, 4 & 5 Conductor 5015 Industrial Equiv. Receptacles



Panel Mount Receptacles | Size 18 | IP67 Rating

F
MIL-SPEC

# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles
3	 18-3 1.1250-18UNEF	North American A. Green/Yellow B. Black C. White	600V 13A	16 AWG	MS18-3MR-PM	MS18-3FR-PM
			300V 10A	18 AWG	MS18-3MR-18-PM	MS18-3FR-18-PM
			300V 4A	22 AWG	MS18-3MR-22-PM	MS18-3FR-22-PM
4	 18-4 1.1250-18UNEF	North American A. Black B. White C. Red D. Green/Yellow	600V 10A	16 AWG	MS18-4MR-PM	MS18-4FR-PM
			300V 5.5A	18 AWG	MS18-4MR-18-PM	MS18-4FR-18-PM
			300V 4A	22 AWG	MS18-4MR-22-PM	MS18-4FR-22-PM
5	 18-5A 1.1250-18UNEF	North American A. White B. Red C. Green/Yellow D. Orange E. Black	600V 8A	16 AWG	MS18-5AMR-PM	MS18-5AFR-PM
			300V 5.5A	18 AWG	MS18-5AMR-18-PM	MS18-5AFR-18-PM
			300V 4A	22 AWG	MS18-5AMR-22-PM	MS18-5AFR-22-PM
	 18-5B 1.1250-18UNEF	North American A. White B. Red C. Green/Yellow D. Orange E. Black	600V 8A	16 AWG	MS18-5BMR-PM	MS18-5BFR-PM
			300V 5.5A	18 AWG	MS18-5BMR-18-PM	MS18-5BFR-18-PM
			300V 4A	22 AWG	MS18-5BMR-22-PM	MS18-5BFR-22-PM

0.3m leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

Specifications:

Shell: Nickel Plated Zinc Diecast
 Insulator: PBT
 Contacts: Copper Alloy with Silver Plating
 Gasket: NBR
 Insert: PBT
 Temperature: -40°C to +105°C (-40°F to +221°F)

