



MIL-SPEC Series Cordsets



3 & 4 Conductor 5015 Industrial Equiv. Cordsets, 16AWG



Straight Male Cordsets | Size 18 | 600 Volt, 13/10 amps | IP67 Rating



F
MIL-SPEC

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MS18-3MP-** (YELLOW) MS18-3MP-**-B (BLACK)	PVC STOOW 3 X 16 AWG 600V, 13A -40°C to 105°C 10mm OD	Industry Standard PVC	North American A. Green/Yellow B. Black G. White	 18-3 1.1250-18UNEF
	MS18P-3MP-**	Yellow PUR AWM 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MS18W-3MP-** (YELLOW) MS18W-3MP-**-B (BLACK)	TPE SEOOW 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Weld Slag Resistant TPE		
	MS18-4MP-** (YELLOW) MS18-4MP-**-B (BLACK)	PVC STOOW 4 X 16 AWG 600V, 10A -40°C to 105C 10.8mm OD	Industry Standard PVC	North American A. Black B. White C. Red D. Green/Yellow	 18-4 1.1250-18UNEF
	MS18M-4MP-**	Yellow PVC STOOW With Foil Shield 4 X 16 AWG 600V, 10A -40°C to 80C 10.8mm OD	Industry Standard PVC Foil Shield		
	MS18W-4MP-**	Yellow TPE SEOOW 4 X 16 AWG 600V, 10A -40°C to 80C 10.8mm OD	Weld Slag Resistant TPE		

** Lengths in meters. Standard Cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated aluminum, for black anodized aluminum coupling nut add a "BA" suffix. (e.g. MS18-3MP-1M becomes MS18-3MP-1M-BA)