



MIL-SPEC Series Receptacles

5, 6 & 10 Conductor 5015 Industrial Equiv. Receptacles



Panel Mount Receptacles | Size 18 | Solder Cup | IP67 Rating

# of Poles	Male Faceview	Rating	Wire AWG	Male Receptacles	Female Receptacles
5	 18-5C 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	MS18-5CMR-PM-SC	MS18-5CFR-PM-SC
	 18-5D 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	MS18-5DMR-PM-SC	MS18-5DFR-PM-SC
6	 18-6 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	MS18-6MR-PM-SC	MS18-6FR-PM-SC
10	 18-10A 1.1250-18UNEF	600V Max 4A Max	16-18 AWG	MS18-10AMR-PM-SC	MS18-10AFR-PM-SC
	 18-10B 1.1250-18UNEF	600V Max 4A Max	16-18 AWG	MS18-10BMR-PM-SC	MS18-10BFR-PM-SC

F
MIL-SPEC

Voltage and Amperage ratings are cable dependent and are based on 600V 16AWG Cable.

Termination made by solder cup.

Specifications:

Shell: Nickel Plated Zinc Diecast
Insulator: PBT
Contacts: Copper Alloy with Silver Plating
Gasket: NBR
Insert: PBT
Temperature: -40°C to +105°C (-40°F to +221°F)

