



MIL-SPEC Series Cordsets

5 Conductor 5015 Industrial Equiv. Cordsets, 16AWG



Straight Female Cordsets | Size 18 | 600 Volt, 8 amps | IP67 Rating



Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MS18-5AFP-**-** MS18-5BFP-**-** MS18-5CFP-**-** MS18-5DFP-**-** (YELLOW)	PVC STOOW 5 X 16 AWG 600V, 8A -40°C to 105°C 13.1mm OD	Industry Standard PVC	North American A. White B. Red C. Green/Yellow D. Orange E. Black	 18-5A 1.1250-18UNEF
	MS18M-5AFP-**-** MS18M-5BFP-**-** MS18M-5CFP-**-** MS18M-5DFP-**-**	Yellow PVC STOOW With Foil Shield 5 X 16 AWG 600V, 8A -40°C to 80°C 13.1mm OD	Industry Standard PVC Foil Shield		 18-5B 1.1250-18UNEF
	MS18P-5AFP-**-** MS18P-5BFP-**-** MS18P-5CFP-**-** MS18P-5DFP-**-**	Yellow PUR AWM 5 X 16 AWG 600V, 8A -40°C to 80°C 13.1mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		 18-5C 1.1250-18UNEF
	MS18W-5AFP-**-** MS18W-5BFP-**-** MS18W-5CFP-**-** MS18W-5DFP-**-**	Yellow TPE SEOOW 5 X 16 AWG 600V, 8A -40°C to 80C 13.1mm OD	Weld Slag Resistant TPE		 18-5D 1.1250-18UNEF

F
MIL-SPEC

** Lengths in meters. Standard Cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated aluminum, for black anodized aluminum coupling nut add a "-BA" suffix. (e.g. MS18-5FP-1M becomes MS18-5FP-1M-BA)

Insert clocking, where available, is indicated by placing 'A, B, C or D' after the pin count in the part number. (e.g. MS18S-5FP-**-** becomes MS18S-5AFP-**-**)