




Profibus-DP Series Receptacles

3 Conductor Profibus-DP Series Receptacles, 22AWG



Front Mount Receptacles | 300 Volt, 4 amps | 12" Leads Version | IP69 Rating




# of Poles	Male Faceview	Color Code	Wire AWG Rating	Threads	Male Receptacles	Female Receptacles
3		PIN #1 - N/C PIN #2 - Green (Tx)D PIN #3 - N/C PIN #4 - Red (Rx)D PIN #5 - Shield	22 AWG 300V 4A	1/2"-14 NPT	PBEC-3MR-2	PBEC-3FR-2
				1/4"-18 NPT	PBEC-3MR-4	PBEC-3FR-4
				PG9	PBEC-3MR-PG9	PBEC-3FR-PG9
				M20	PBEC-3MR-M20	PBEC-3FR-M20

12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

For 1/2" receptacles with lengths of 15" or longer O-ring and jam nut are included.


Stainless Steel versions are available, add "-SS" suffix to the part number (e.g. PBEC-3MR-2-SS).

1/2"-14NPT Threads




Male Receptacle

1/4"-18NPT Threads




Male Receptacle

PG9 Threads




Male Receptacle


M20 Threads




Male Receptacle




Female Receptacle



Female Receptacle



Female Receptacle



Female Receptacle

Specifications:

Shell: 1/2" -14 NPT: Clear Anodized Aluminum
1/4" -18 NPT: Nickel Plated Brass
PG 9: Nickel Plated Brass
M20: Clear Anodized Aluminum
Insulator: Polyamide

Contacts: Copper Alloy with Gold Plating
O-Ring: NBR
Lock Nut: Zinc Plated Steel
Jam Nut: Nickel Plated Brass
Temperature: -40°C to 80°C (-40°F to +221°F)

Profibus-DP Series

N