



Cable Glands

Metric Threads Cable Glands



Explosion-Proof Plastic Cable Glands | Metric Threads | IP66 Rating

Part Number	Color	Diameter Range (mm)	A Mounting Hole Clearance (mm)	B Thread Length (mm)	C Wrench Flats (mm)	Thread Type
PCGEX-M12-B	Black	4 - 7	12.2	8	15	M12 x 1.5
PCGEX-M12L-B	Black	4 - 7	12.2	12	15	M12 x 1.5
PCGEX-M16-B	Black	5.5 - 10	16.2	8	20	M16 x 1.5
PCGEX-M16L-B	Black	5.5 - 10	16.2	12	20	M16 x 1.5
PCGEX-M20-B	Black	5.5 - 13	20.2	8	24	M20 x 1.5
PCGEX-M20L-B	Black	5.5 - 13	20.2	13	24	M20 x 1.5
PCGEX-M25-B	Black	8 - 17	25.2	8	29	M25 x 1.5
PCGEX-M25L-B	Black	8 - 17	25.2	13	29	M25 x 1.5
PCGEX-M32-B	Black	12 - 21	32.2	10	36	M32 x 1.5
PCGEX-M40-B	Black	17 - 28	40.2	10	46	M40 x 1.5
PCGEX-M50-B	Black	22 - 35	50.2	12	55	M50 x 1.5
PCGEX-M63-B	Black	27 - 48	63.2	12	68	M63 x 1.5

Intrinsically safe explosion proof versions are also available, please consult the factory.

Protection type EExd e II is a standard European classification.

These specifications are NOT intended to be correlated to or to be a substitution for U.S. Explosion-Proof ratings.

Type of protection EExd e II- increased safety.

Permanent ambient temperature -50°C to +55°C (-58°F to +131°F).

Protection type is IP66 according to EN 60529.

Certificate of conformity: PTB-No.

Ex-92-C.3142; PTB-No. Ex-92.C3108X (M12 & M16).

Locking Nuts must be ordered separately.

Materials: ALCRYM

