



MATERIALS:			
BODY:	BLACK POLYAMIDE		
CONTACTS:	GOLD PLATED COPPER ALLOY		
CABLE SEAL:	NBR		
INSERT:	PBT		
COUPLING:	NICKEL PLATED BRASS		
RATINGS:			
	AWG	CABLE RATED <75°C	CABLE RATED 75°C+
AMPS:	10AWG	32A	40A
	12AWG	25A	30A
	14AWG	20A	24A
VOLTS:	600VAC MAX		
CABLE RANGE:	10 AWG - 14AWG		
STOW, STOOW (US)	.530"-.576" (13-15mm) Gray Grommet		
	.542"-.707" (13-18mm) Black Grommet		
TC-ER (US)	.468"-.509" (12-13mm) Gray Grommet		
	.502"-.509" (12-13mm) Black Grommet		
SEOOW (US)	.516"-.630" (13-16mm) Gray Grommet		
	.516"-.7185" (13-18mm) Black Grommet		
STOW, STOOW (CN)	.542"-.707" (13-18mm) Black Grommet		
SEOOW (CN)	.516"-.718" (13-18mm) Black Grommet		
SCCR RATING:	65kA Breakers and Fuses		
RoHS COMPLIANT:	Yes		
PROTECTION:	IP67		
UL CATEGORY:	PVVA (US), PVVA7 (Canada)		
U.S.	UL 2237 LISTED, File E469485		
CANADA	C-JUL 2237 LISTED, File E469485		

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminal

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	JJH
	DRAWN DATE	12/03/2020
	CHECKED BY	GO
	CHECK DATE	12/07/2020
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
SIZE	DWG. NO.	REV
B	PMIN-4MP-FW	A
SCALE: 3:2	WEIGHT:	SHEET 1 OF 1