




T35 DIN Rail Interface Modules


Ethernet Connector DIN Rail Modules, 30-14AWG




RJ45 to Terminal Block | RJ45 to RJ45 | 250V, 1.5amps

Connection Type A	Connection Type B	Wire Range	Features	Part Number	
				Marker Tag	No Marker Tag
RJ45	RJ45	30-14AWG Solid or Stranded (0.05mm ² - 2.5mm ²)	Shielded Sockets Connected pin to pin 35mm DIN rail mounting	T35-RJ45-RJ45-MC	T35-RJ45-RJ45
Vertical RJ45	Vertical RJ45			T35-RJ45V-RJ45V-MC	T35-RJ45V-RJ45V
RJ45	Spring Clamp Terminal Block			T35-RJ45-TBS-MC	T35-RJ45-TBS


The printed circuit boards have component holes for the easy addition of LED's, resistors, or other electronic components. Other configurations are available. Please consult factory.




RJ45 to RJ45
with 3 Removable Marker Tags




Vertical RJ45 to Vertical RJ45
with 3 Removable Marker Tags




RJ45 to Spring Clamp Terminal Block
with 3 Removable Marker Tags



RJ45 to RJ45



Vertical RJ45 to Vertical RJ45



RJ45 to Spring Clamp Terminal Block

Specifications:

Body: Polyamide
Screw: Galvanized Steel
Terminal: Tin-Plated Brass
Clamp: Nicked Brass
Insulators: Glass-Filled Thermoplastic
Contacts: Gold-Plated Copper Alloy

Marker Tags: Polyamide
Wire Strip Length: 0.3in (6.7mm)
Screw Torque: 4.4lbf-in (0.5Nm)
Screw Size: 4-40
Temperature: -40 °C to 105 °C