



Model SLM700 shown with mounting base options
(ordered separately)

► Model SLM700

StreamLine® Modular Electronic Sounder

Model SLM700 is a multifunctional electronic sounder developed with a multiple input technology that produces two different tones (one per channel), controllable via independent electric contacts.

There are 64 unique tones to select from across two switches (32 tones per switch). The volume of the tone is adjustable between 86-105 dBa @ 1m at three output levels (high, medium, low) through an integrated button. Model SLM700 body material is a self-extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
- PLC compatible with PNP or NPN connections (Except Dock Base, only NPN)
- Choice of 64 selectable tones (32 per input selectable via DIP switch)
- Produces two tones at three adjustable tone levels
- Adjustable volume between 76 dBa to 95 dBa @10' (86-105 dBa @ 1m)
- Seven mounting base options
- Type 3R, IP65 enclosure
- CE and UKCA compliant
- UL and cUL Listed

*Voltage is dependent on selected base (sold separately).

MODEL	VOLTAGE	DECIBELS MIN.-MAX.		MAXIMUM OPERATING CURRENT (mA)					
		10'	1M	12VDC	24VDC	12VAC	24VAC	120VAC	240VAC
SLM700 *	12-24VAC/DC or 120-240VAC	76-95	86-105	85	60	280	190	125	90

*For body color, indicate GY for Gray or R for Red.


Weight (unit(s) + base = total weight)

SLM700	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT	2-STACK DOCK BASE	3-STACK DOCK BASE
7.76 oz 0.22 kg	12-24VAC/DC	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg	14.46 oz 0.41 kg	21.16 oz 0.60 kg
	120-240 VAC	—	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg	16.58 oz 0.47 kg	24.69 oz 0.70 kg

StreamLine® Modular Electronic Sounder (SLM700)

SPECIFICATIONS

Operating Temperature: -40°F to 131°F -40°C to 55°C



SLMB23W



SLMB23N



SLM-RR



SLMB23V







ACCESSORIES FOR DOCK BASE

HOW TO ORDER

- Specify model number:
SLM700GY - Gray body
SLM700R - Red body
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG1)
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base
Wall Mount Bracket (SLMB23W)
1/2" NPT Adaptor (SLMB23N)
Retaining Ring (SLM-RR)
Light Visor (SLMB23V)

MOUNTING BASE OPTIONS

Mounting bases are rated Type 4X. Final product rating is determined by top module. In combination with SLM700, the unit is Type 3R, IP65. For added protection, install with included retaining ring (SLM-RR).

 Shallow Base	Model Number	Base Color	Voltage	
	SLMBS-012-024GY	Gray	12-24VAC/DC	
 Deep Base	SLMBS-012-024R	Red	12-24VAC/DC	
	SLMBD-012-024GY	Gray	12-24VAC/DC	
	SLMBD-012-024R	Red	12-24VAC/DC	
	SLMBD-120-240GY	Gray	120-240VAC	
 Wall Mount	SLMBD-120-240R	Red	120-240VAC	
	SLMBW-012-024GY	Gray	12-24VAC/DC	
 Pipe Mount	SLMBW-120-240GY	Gray	120-240VAC	
	SLMBP-012-024GY*	Gray	12-24VAC/DC	
 Twin Wall Mount	SLMBP-120-240GY*	Gray	120-240VAC	
	SLMBT-012-024GY	Gray	12-24VAC/DC	
 2-Stack Dock Base  3-Stack Dock Base	SLMBT-120-240GY	Gray	120-240VAC	
	SLMB2-024GY*	Gray	24VAC/DC	
	SLMB2-120-240GY*	Gray	120-240VAC	
	SLMB3-024GY*	Gray	24VAC/DC	
Note: Dock bases allow one function per position and include visors. Dock bases are NPN compatible only.				

*Installation of included retaining ring is required for pipe and dock bases.

Rev. B