



01	03-02-06	JH		RELEASED TO PRODUCTION	02055-47				
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH	

RISER RATED - FSDR936Y			
TENSILE LOAD		BEND RADIUS	
INSTALLATION	LONG TERM	INSTALLATION	LONG TERM
1320 N (300 lbf)	330 N (74 lbf)	390 mm (15.4 in)	195 mm (7.7 in)
CABLE DIAMETER (REFERENCE ONLY)	TEMPERATURE		
	INSTALLATION/OPERATION		STORAGE
19.5mm Dia. (.77")	-20° C TO +50° C -4° F TO +122° F		-40° C TO +65° C -40° F TO +149° F

NOTES:

1. DIAMETER DIMENSION SHOWN FOR REFERENCE ONLY.
2. CABLE SUPPLIED IN 2500 METER (8202 FT) LENGTHS.
3. FOR PART NUMBERS AND LENGTHS OTHER THAN THOSE SHOWN, CONTACT YOUR PANDUIT SALES PERSON.
4. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTIONS OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

PANDUIT™
CORP.
TINLEY PARK, ILL 60477

ALL DIMENSIONS ARE GIVEN IN INCHES.
UNLESS OTHERWISE SPECIFIED.

DIMENSIONAL TOLERANCES ARE:

(.X) (.XXX) ± .010 | 0.3
(.XX) ± .03 | 0.8 | ANGLES

REVIEW DRAWING NUMBERS

1	
---	--

7	

02055-47	A
----------	---