

Universal Network Zone System

SPECIFICATIONS

The universal network zone system shall include copper/fiber uplinks and downlinks optimized for industrial Ethernet switches. System shall incorporate redundant power supplies and optional UPS and PoE power supply. The enclosure shall be UL 508A, UL Type 4/12/4X, IP66 rated and CE. A removable, pre-engineered back plate with DIN rails shall be incorporated in the enclosure. Pre-installed accessory side panels, fiber slack spool, and L rings shall be included for cable management. The door shall be secured with 3mm double bit or slotted latch drive feature. The door shall hinge on the right or left. Class 2 power circuits shall be pre-wired, labeled, and tested. A barrier shall be present to isolate IT personnel from high voltage power circuit.



TECHNICAL INFORMATION

Standards:	UL 508A Standard for Industrial Control Panels, UL Type 4/12 or 4X, IP66 Rated, CE
Dimensions H x W x D:	Z23U: 36.0 in. x 24.0 in. x 11.7 in. (914mm x 610mm x 297mm) Z22U: 24.0 in. x 24.0 in. x 11.7 in. (610mm x 610mm x 297mm)
Color and material:	Enclosures: Gray, 14 gauge cold roll steel or 316 stainless steel Back panels: 14 gauge galvanized steel or 304 stainless steel
Thermal analysis:	Validated to 40°C ambient outside of enclosure or 60°C maximum within enclosure at up to 95% (non-condensing) humidity
Installation:	Wall mount with optional outside-mount flange

KEY FEATURES AND BENEFITS

Switch ready solution:	Reduces time required for planning, designing, procurement, and installation, resulting in simpler specification and up to 75% faster implementation
Universal design:	Works with most DIN mount industrial Ethernet switches, providing design flexibility
Designed to accept customer supplied industrial switches:	Offer management and diagnostics from within IT and controls environments to optimize network traffic
Copper/fiber uplinks or patch field and copper/fiber connectivity:	Enables troubleshooting of network connections and verification of field terminations
Included redundant power supplies:	Minimize the risk of equipment failure for improved network reliability
Optional maintenance-free UPS:	Prevents rebooting of switch and loss of network during power outages
Optional PoE:	Provides 48 VDC power to the switch for PoE devices to simplify PoE capable deployments and save money on the purchase of PoE injectors
Isolation barrier:	Segregates higher line voltage from lower voltage switch for increased safety
Bonding provisions and grounding bar:	Ensure path to ground to protect personnel and equipment
Part number configurator:	Available to create custom part number for a specific Zone Application Auto generates part number, price and lead time, and you can configure multiple options (see page 4)
Detailed installation guide:	Provides easy, repeatable design instructions assuring consistency and saving time on the job-site

Universal Network Zone System

24" x 36": Z23U	Part numbers available through Panduit Configurator Tool
24" x 24": Z22U	Part numbers available through Panduit Configurator Tool

Related Products

PanZone[®] NEMA 4X Rated Drain Kit

Drain kit:	PZNDVK
-------------------	--------

Category 6 UTP bulkhead connector:	IAEBH6
---	--------

Category 6 STP bulkhead connector:	IAEBH6S
---	---------

Fiber Uplink Accessories

Surface mount fiber box:	CBXF6BL-AY
---------------------------------	------------

LC OptiCam[®] connector:	FLCDMCXAQY
--	------------

LC connector module:	CMDSAQLCZBL
-----------------------------	-------------

LC OM3 patch cord:	FX2ERLNLNSNM001
---------------------------	-----------------

Opti-Core[®] interlocking armored cable:	FOPRX12Y
--	----------

DIN Rail Patching Accessories

IndustrialNet[™] 8-port DIN rail mount copper patch panel:	CDPP8RG
--	---------

IndustrialNet[™] 8-port DIN rail fiber optic enclosure:	FDPPSIG
---	---------

Mini-Com[®] single port DIN rail mount adapter:	CADIN1IG [^]
---	-----------------------

Copper Connectivity

UTP patch cord:	UTP28SP3
------------------------	----------

UTP Mini-com[®] jack:	CJ688TGIW
---------------------------------------	-----------

STP patch cord:	STP28X1MIG
------------------------	------------

STP Mini-com[®] jack:	CJS6X88TGY
---------------------------------------	------------

TX6500[™] Copper Cable

Category 6, UTP:	PUR6504BU-ULP
-------------------------	---------------

[^]For standard colors other than International Gray, replace IG in part number with BL (Black), EI (Electric Ivory), IW (Off White), or WH (White).

Universal Network Zone System

APPLICATIONS

The Panduit Universal Network Zone System is designed to rapidly deploy an industrial Ethernet network between the enterprise and plant floor. Copper/fiber connectivity and power features minimize engineering and installation time resulting in faster implementation. The Universal Network Zone System provides usability similar to IT switches for any customer owned industrial switch to be deployed on the plant floor. This ensures that management and control of the network does not impede effective network data usage. With UL Type 4/12/4X, IP66 rating and CE, the enclosures provide reliability and high performance, as an integral component of the end-to-end solution for Industrial Networks.

PROVIDED WITH Z23U ENCLOSURES:

- Downlink port connectivity – sixteen Category 6 UTP jacks and patch cords
- Downlink patch field – 19 in. 48-port patch panel (CPP48WBLY)
- Uplink port connectivity – six LC adaptors, four LC OM3 patch cords
- Power infrastructure – redundant 24 VDC dc power supplies and optional UPS, PoE
- Power input – 100 – 250 VAC single phase
- DIN rail mounting – three 16.7 in. long DIN rails
- Cable management – 7 in. deep strain relief bar and adjustable ring managers
- Isolation barrier to cover high voltage equipment on lower DIN rail

Customer Supplied: accepts up to two user-defined industrial DIN mount switches with max dissipation of 42 Watts at 24 VDC


More options available at panduit.com/networkzone



24" x 36"

ENGINEERING DRAWINGS

Z23U



The configuration will change depending on the selectors.

Dimensions are in inches. [Dimensions in brackets are metric].

Universal Network Zone System

PROVIDED WITH Z22U ENCLOSURES:

- Downlink port connectivity – eight Category 6 UTP jacks and patch cords
- Downlink patch field – one 8-port patch panel (CDPP8RG)
- Uplink port connectivity – six LC adaptors, two LC OM3 patch cords
- Power infrastructure – redundant 24 VDC dc power supplies and optional UPS, PoE
- Power input – 100 – 250 VAC single phase
- DIN rail mounting – two 16.7 in. long DIN rails
- Cable management – 7 in. deep strain relief bar and adjustable ring managers
- Isolation barrier to cover high voltage equipment on lower DIN rail

Customer Supplied: accepts one user-defined industrial DIN mount switch with max dissipation of 42 Watts at 24 VDC


More options available at panduit.com/networkzone




24" x 24"

ENGINEERING DRAWINGS

Z22U



AC Cover Removed for Clarity



AC Cover Removed for Clarity
Electrical Wiring Not Shown

The configuration will change depending on the selectors.

Dimensions are in inches. [Dimensions in brackets are metric].

Universal Network Zone System

CONFIGURATION AND ORDERING TOOL

- 1 **Configure product:** Select your universal network zone system configuration options
- 2 **Get part number, price and lead time:** Get real time MSRP quote with lead time
- 3 **Order:** Log in and place your order!

**EASY TO
CONFIGURE,
PRICE & ORDER!**

Questions?
Contact Panduit
technical support at
800.777.3300

PANDUIT CPQ

Configure Universal Zone Enclosure

Update

Start Over

Add to Cart

Add to Quote

Enclosure

Size (W x H)

24" x 36" (610mm x 915mm)

Material

Mild Steel

Sloped Top

No

Handle

Standard Quarter Turn Latch (NEMA 4/4X/12)

Switches

Customer Switches

2

Options

PoE Type

None

Power Type

RPS, One Panduit Maintenance-Free 100W UPS per Switch (100...

Copper Connection Type

UTP with Patch Panel

Number Copper Cord/Jacks

16

Fiber Uplink Patch Panel

6-port Surface Mount

Fiber Uplink Media Type

OM3

Number Fiber Cords

4



Universal Network Zone System, 24" x 36", mild steel, with standard latch, for two customer supplied Industrial switches, (16) UTP Cat 6 patch cords and jacks for downlinks with patch panel, (4) MM OM3 fiber cords for uplinks, 6-port fiber

Part Drawings

Specification Sheets

C-ZCUNV-ENCLOSURE-OC-CI--ENG.pdf

C-ZCUNV-ENCLOSURE-OC-CQ--ENG.pdf

C-ZCUNV-POWER-OC-EBI--ENG.pdf

C-ZCUNV-POWER-OC-EBM--ENG.pdf

MULTIPLE OPTIONS AVAILABLE TO CONFIGURE THE CUSTOM SYSTEM IDEAL FOR YOUR APPLICATION:


Size H x W:	24 in. x 24 in. 36 in. x 24 in.
Enclosure options:	Mild steel, 316 stainless steel, sloped top option
Handle:	Standard latch, key locking handle, padlocking handle
Switch quantity:	1 or 2
PoE type:	Separate or combined PoE input
Power:	Single power supply, redundant power supplies, maintenance-free ultra capacitor UPS, battery UPS, no UPS
Cabling and connectivity:	Unshielded copper with plastic patch panel, shielded copper with metal patch panel, 4 – 48 jacks and patch cords in multiples of 4
Uplink options:	6 or 12-port surface mount box, 6 or 12-port fusion splice, SM, OM1, OM3, OM4, 2 – 12 Fiber Patch Cords in multiples of 2

panduit.com

Universal Network Zone System

DEPLOYING ZONE NETWORK TOPOLOGY

The Panduit building block architecture for industrial networks is a highly effective way to deploy industrial Ethernet solutions in a plant floor environment. Panduit's network zone systems building block helps to deploy industrial switches and provide a platform to improve manageability, localize network traffic, and limit Layer 2 broadcast domains[‡]. The network zone systems allow all cables within a cell/area zone to be managed and patched within a single enclosure. By using a zone cabling architecture, network cabling becomes easier to locate, manage, and maintain because each additional device is routed within the same pathways and enclosure. Managed cabling decreases the number of home runs throughout a facility and reduces abandoned cable in plenum spaces, to make the workplace run more efficiently and safely.



Following a zone topology with the Panduit building block architecture creates a highly scalable and flexible network deployment.

[‡]For additional reference see the Panduit Popular Configuration Drawing "Overview of Industrial Switch Deployment" PCD0001