

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N
P24D34M-XXYZ

WEIGHT
SEE SHEET 2

SPECIFICATION:

1. STANDARD:
- | | |
|----------------------|-----------------------------------|
| UNIT TYPE: | MONITORED INPUT |
| ORIENTATION: | VERTICAL, 0U FULL |
| OUTLET QTY & TYPE: | (12) C13, (12) C19 |
| INPUT VOLTAGE: | 200-240VAC |
| INPUT CURRENT: | 60A (48A DERATED) |
| JAPAN INPUT CURRENT: | 60A |
| BREAKER QTY & TYPE: | (6) 20AMP, DOUBLE-POLE |
| INPUT PHASE: | THREE-PHASE, DELTA |
| RATED POWER: | 17.3 kVA |
| INPUT PLUG: | IEC 60309 3P+E 9H 60A |
| INPUT POWER CORD: | SEE SHEET 2 FOR PART NUMBER TABLE |
| REGULATORY STANDARD: | RoHS COMPLIANT |
2. ADDITIONAL:
NONE
3. ACCESSORIES:
(1) QUICK-START GUIDE

NOTES:

1. PRIMARY DIMENSIONS ARE IN MILLIMETERS. SECONDARY DIMENSION ARE IN [INCHES] .
2. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES .
3. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART .
4. FOR FULL PRODUCT FUNCTIONALITY REFER TO USER MANUAL .
5. DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP END FED" CONFIGURATION

IDENTIFICATION

FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE SHEET 2 CONFIGURABLE PART NUMBERS: P24D34M-XX Y Z

XX: FINISHED GOOD COLOR
BL =BLACK
RD =RED
WH =WHITE
YL =YELLOW
BU =BLUE
GN =GREEN


Y: INPUT FEED TYPE
1 =TOP-END FED
2 =BOTTOM-END FED

Z: INPUT CORD LENGTH
A =1 METER
B =2 METER
C =3 METER

BOTTOM VIEW

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX.
THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY

SIGN
DATE
PRINT

TITLE		INTELLIGENT SERIES PDU P24D34M-XXYZ CUSTOMER DRAWING	
ITEM REVISION NAME		PANDUIT	
DATASHEET FILE NAME:			
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN] Tolerance(mm) 0<L<50 ±0.5 50<L<250 ±1.0 250<L<500 ±1.5 500<L<1000 ±2.5 1000<L<2000 ±4.0		MATERIAL/COLOR: N/A	
 THIRD ANGLE PROJECTION		DRAWING NUMBER: P24D34M_DC	
DRAWN BY WSJ	DATE 07/17/2017	CHK SEAN	SCALE NONE
SHT 1 OF 2		SCALE B	

LEFT VIEW

REAR VIEW

RIGHT VIEW

FRONT VIEW

1555.0 [61.22"]

(4) PL 32.0 [1.26"]

40.5 [1.59"]

24.0 [.94"]

24.0 [.94"]

40.5 [1.59"]

24.0 [.94"]

24.0 [.94"]

(2) PL Ø18.4 [Ø.72"]

TOOLESS MOUNTING
BUTTON LOCATIONS (12) PL

1555.0 [61.22"]

40.5 [1.59"]

24.0 [.94"]

24.0 [.94"]

53.0 [2.09"]

1555.0 [61.22"]

(4) PL 32.0 [1.26"]

FOR LENGTH
SEE SHEET 2
PART NUMBER
TABLE.

20 AMP,DOUBLE-POLE ELECTRO
MECHANICAL SWITCH / BREAKER
(6) PLACES

B1 B2 B3 B4 B5 B6

B1 [DARK GRAY] B2 [LIGHT GRAY] B3 WHITE B4 [DARK GRAY] B5 [LIGHT GRAY] B6 WHITE

1750.0 [68.90"]

52.0 [2.05"]

75.0 [2.95"]

PLUG/RECEPTACLE BLOCK



PLUG
IEC 60309, 3P 4W, 9H
IP44 (SPLASHPROOF)
60A, 250V, 3 - PHASE MAX RATED INPUT
48A DERATED



RECEPTACLES
IEC 60320/C19
16A, 250V MAX RATED OUTPUT



RECEPTACLES
IEC 60320/C13
10A, 250V MAX RATED OUTPUT

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
03C	01/15/2021	huang	MIM	JAWI	ADD JAPAN INPUT CURRENT	P24D34M
03B	07/06/2020	CWW	MIM	JAWI	UPDATED THE OUTLET DESIGN	P24D34M
02B	06/21/2019	WKM	MIM	JAWI	UPDATE PLUG DESCRIPTION IN PLUG/RECEPTACLE BLOCK	P24D34M
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO I NCLUDE CONFIGURABLE OPTION 'DE-CODER'	P24D34M
01A	07/17/2017	WSJ	MIM	EDM	INITIAL RELEASE	P24D34M



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P24D34M	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-BL1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-BL1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-RD1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-RD1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-RD1C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-WH1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-WH1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-WH1C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-YL1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-YL1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-YL1C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-BU1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-BU1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-BU1C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-GN1A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-GN1B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-GN1C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , TOP-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-BL2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-BL2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-BL2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-RD2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-RD2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-RD2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-WH2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-WH2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-WH2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-YL2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-YL2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-YL2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-BU2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-BU2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-BU2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg
P24D34M-GN2A	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3' [+3.5"/-1.75"]	11.3kg
P24D34M-GN2B	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5' [+7"/-3.5"]	12.5kg
P24D34M-GN2C	VERTICAL,(12) C13,(12)C19,MONITORED INPUT, 200-240V/60A/3 PHASE DELTA , BOTTOM-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10' [+10"/-5"]	13.7kg

B

B

A

A

03C	01/15/2021	huang	MIM	JAWI	ADD JAPAN INPUT CURRENT	P24D34M
03B	07/06/2020	CWW	MIM	JAWI	UPDATED THE OUTLET DESIGN	P24D34M
02B	06/21/2019	WKM	MIM	JAWI	UPDATE PLUG DESCRIPTION IN PLUG/RECEPTACLE BLOCK	P24D34M
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO I NCLUDE CONFIGURABLE OPTION 'DE-CODER'	P24D34M
01A	07/17/2017	WSJ	MIM	EDM	INITIAL RELEASE	P24D34M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN



WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN DATE PRINT	
TITLE INTELLIGENT SERIES PDU P24D34M-XXYZ CUSTOMER DRAWING			
ITEM REVISION NAME			
DATASHEET FILE NAME:			
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR: N/A	
THIRD ANGLE PROJECTION		DRAWING NUMBER: P24D34M_DC	
DRAWN BY WSJ	DATE 07/17/2017	CHK SEAN	SCALE NONE
SHT 2 OF 2			SCALE B