



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


PANDUIT P/N	WEIGHT
P24D07M-XXYZ	SEE SHEET 2




LEFT VIEW



REAR VIEW



RIGHT VIEW



FRONT VIEW

SPECIFICATION:


1. STANDARD:
- | | |
|----------------------|-----------------------------------|
| UNIT TYPE: | MONITORED INPUT |
| ORIENTATION: | VERTICAL, MID |
| OUTLET QTY&TYPE: | (20)C13, (4)C19 |
| INPUT VOLTAGE: | 200-240VAC |
| INPUT CURRENT: | 30A (24A DERATED) |
| BREAKER QTY&TYPE: | (2) 20AMP, DOUBLE-POLE |
| INPUT PHASE: | SINGLE-PHASE |
| RATED POWER: | 5.0kVA |
| INPUT PLUG: | NEMA L6-30P |
| INPUT POWER CORD: | SEE SHEET 2 FOR PART NUMBER TABLE |
| REGULATORY STANDARD: | RoHS COMPLIANT |
2. ADDITIONAL:
- NONE
3. ACCESSORIES:
- (1) QUICK-START GUIDE

NOTES:

- PRIMARY DIMENSIONS ARE IN MILLIMETERS. SECONDARY DIMENSION ARE IN [INCHES]
- INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES
- VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
- FOR FULL PRODUCT FUNCTIONALITY REFER TO USER MANUAL
- DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP END FED" CONFIGURATION

IDENTIFICATION


FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE SHEET 2 CONFIGURABLE PART NUMBERS: P24D07M-XX Y Z



BOTTOM VIEW

XX: FINISHED GOOD COLOR BL=BLACK RD=RED WH=WHITE YL=YELLOW BU=BLUE GN=GREEN	Y: INPUT FEED TYPE 1=TOP-END FED 2=BOTTOM-END FED	Z: INPUT CORD LENGTH A=1 METER B=2 METER C=3 METER
---	---	---

PLUG/RECEPTACLE BLOCK



PLUG
NEMA L6-30P, 2P 3W
30A, 250V MAX RATED INPUT
24A DERATED




RECEPTACLES
IEC 60320/C19
16A, 250V MAX RATED OUTPUT



RECEPTACLES
IEC 60320/C13
10A, 250V MAX RATED OUTPUT

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
03A	07/16/2020	CWW	MIM	JAWI	UPDATED THE OUTLET DESIGN	P24D07M
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO INCLUDE CONFIGURABLE OPTION 'DE-CODER' UPDATED CIRCUIT BREAKER LABELS WITH ROTATED TEXT	P24D07M
01A	07/27/2017	GEORGE	MIM	EDM	INITIAL RELEASE	P24D07M

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY				SIGN										
				DATE										
				PRINT										
TITLE														
INTELLIGENT SERIES PDU P24D07M-XXYZ CUSTOMER DRAWING														
ITEM REVISION NAME:														
DATASHEET FILE NAME:														
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]														
 THIRD ANGLE PROJECTION Tolerance(mm) <table><tr><td>0<L<50</td><td>±0.5</td></tr><tr><td>50<L<250</td><td>±1.0</td></tr><tr><td>250<L<500</td><td>±1.5</td></tr><tr><td>500<L<1000</td><td>±2.5</td></tr><tr><td>1000<L<2000</td><td>±4.0</td></tr></table>				0<L<50	±0.5	50<L<250	±1.0	250<L<500	±1.5	500<L<1000	±2.5	1000<L<2000	±4.0	MATERIAL/COLOR: N/A
0<L<50	±0.5													
50<L<250	±1.0													
250<L<500	±1.5													
500<L<1000	±2.5													
1000<L<2000	±4.0													
				DRAWING NUMBER: P24D07M_DC										
DRAWN BY	DATE	CHK	SCALE	SHT 1 OF 2	SCALE B									
GEORGE	07/27/2017	SEAN	NONE											



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P24D07M	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-BL1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-BL1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-RD1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-RD1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-RD1C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-WH1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-WH1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-WH1C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-YL1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-YL1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-YL1C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-BU1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-BU1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-BU1C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-GN1A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-GN1B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-GN1C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , TOP-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-BL2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, BLACK	BLACK (RAL 9005)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-BL2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, BLACK	BLACK (RAL 9005)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-BL2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-RD2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, RED	RED (RAL 3020)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-RD2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, RED	RED (RAL 3020)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-RD2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, RED	RED (RAL 3020)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-WH2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, WHITE	WHITE (RAL 9003)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-WH2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, WHITE	WHITE (RAL 9003)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-WH2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, WHITE	WHITE (RAL 9003)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-YL2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-YL2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-YL2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, YELLOW	YELLOW (RAL 1023)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-BU2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, BLUE	BLUE (RAL 5005)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-BU2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, BLUE	BLUE (RAL 5005)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-BU2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, BLUE	BLUE (RAL 5005)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg
P24D07M-GN2A	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 1 METER INPUT CORD, GREEN	GREEN (RAL 6001)	1M(+178MM-89MM) 3.3'[*+3.5"/-1.75"]	6.4kg
P24D07M-GN2B	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 2 METER INPUT CORD, GREEN	GREEN (RAL 6001)	2M(+178MM-89MM) 6.5'[*+7"/-3.5"]	6.6kg
P24D07M-GN2C	VERTICAL,(20) C13,(4) C19,MONITORED INPUT, 200-240V/30A/1 PHASE , BOTTOM-END FED, 3 METER INPUT CORD, GREEN	GREEN (RAL 6001)	3M(+254MM-127MM) 10'[*+10"/-5"]	6.8kg

B

B

A

A

03A	07/16/2020	CWW	MIM	JAWI	UPDATED THE OUTLET DESIGN	P24D07M
02A	06/07/2018	H.XU	MIM	JAWI	ADDED SHEET 2 WITH CONFIGURABLE PART NUMBER TABLE AND DESCRIPTION UPDATED IDENTIFICATION TO INCLUDE CONFIGURABLE OPTION 'DE-CODER' UPDATED CIRCUIT BREAKER LABELS WITH ROTATED TEXT	P24D07M
01A	07/27/2017	GEORGE	MIM	EDM	INITIAL RELEASE	P24D07M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN	
		DATE	
		PRINT	
TITLE INTELLIGENT SERIES PDU P24D07M-XYZ CUSTOMER DRAWING			
ITEM REVISION NAME:			
DATASHEET FILE NAME:			
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR: N/A	
 THIRD ANGLE PROJECTION		DRAWING NUMBER: P24D07M_DC	
DRAWN BY GEORGE	DATE 07/27/2017	CHK SEAN	SCALE NONE
SHT 2 OF 2		SCALE B	

