



Representative Image

Catalog No. 2TLA050011R1433

Description: "MKEY8, SOL NPT, 110V MET. FLEX KEY"

UPC No 804325833448

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and head, spring lock (power to unlock), 2000N holding force. 110VAC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with metal flex key.

Descriptors

Category	Safety Sensors, Switches, Locks & Gate Boxes
Type	Safety Lock

Specifications

Product Class	Safety Locks & Process Locks
Product Main Type	MKey
Supply Voltage	110VAC
Outputs	Contact
Number of Outputs	4NC + 2NO
Degree of Protection	IP67

Classifications

ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions

Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Width	46 mm
Product Net Weight	0.78kg

Safety Information

Performance Level	Up to e
-------------------	---------



