



## Catalog No. TLQ412RT1

**Description: 125A 4CRT 1P3W 120/240V 3R W/GROUND**

**UPC No 783164680171**

**Home > Load Centers > Load Centers**

ReliaHome T-Series main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLQ412RT1 features space for 4, 1" breakers, a 125 A bus ampere rating, a factory included ground bar, and an outdoor suitable enclosure.

### Descriptors

Category	Load Centers
GO Schedule	RA
Grouping	Single Phase - USA

### Specifications

# Branch Circuit 250A	4
1" Space	4
1/2" Space	0
Amperage	125 A
Circuit Breaker Style	Pigtail (non-PON)
Device type	Main Lug
Door	Yes
Enclosure	Outdoor
Enclosure Type	Outdoor, Surface Mount
Factory Installed Ground Kit	Yes
Feed	Either
Input/Output Voltage	120/240V ac
Interrupting Capacity Rating	22
Load Center Type	T-Series (non-PON)
Meter Socket Options: 200 Amp Main Breaker Installed	No
Meter Socket Options: High Amp Mode	None
NEMA Rating	NEMA 3R
Phase	1 Phase
Service & Voltage	1 Phase, 3 Wire, 120/240V ac
Wires	3 Wire

### Classifications

UL/CUL Listing	UL
----------------	----

