MATERIAL NO.	ENGINEERING NO.	FINISHED LENGTH
1300250196	DN99A-M006	1 FT 11.6 IN (0.6M)
1300250220	DN99A-M400	131 FT 2.8 IN (40.0M)
1300250223	DN99A-M750	246 FT (75.0M)

B

CABLE LENGTH TOLERANCES
<.3M [1FT]: +19mm-0 [+.75in-0]
.3 - .9M [1 - 3FT]: +44.5mm-0 [+1.75in-0]
.9 - 1.8M [3 - 6FT]: +55.6mm-0 [+2.19in-0]
1.8 - 3.7M [6 - 12FT: +88.9mm-0 [+3.50in-0]
3.7 - 7.3M [12 - 24FT]: +165.1mm-0 [+6.50in-0]
7.3-14.6M [24 - 48FT]: +317.5mm-0 [+12.50in-0]
14.6 - 30.5M [48-100FT]: +622.3mm-0 [+24.50in-0]
OVER 30M [100FT] +2% OF FINISHED LENGTH

PART NO. MATRIX

DN99A-M010

FINISHED LENGTH
M005= 0.5 METER
M010= 1 METER
M100= 10 METER

WIRING DIAGRAM

P1		S2
1	DRAIN	1
2	RED +V	2
3	BLACK -V	3
4	WHITE CAN H	4
5	BLUE CAN L	5

NOTES:
1. MATERIAL: AS NOTED
2. FINISH: AS NOTED
3. ELECTRICAL SPECIFICATIONS
   VOLTAGE RATING: 300V PER IEC60664
   300V PER UL2238
   CURRENT RATING: 4A
4. TEMP RANGE: -20°C TO +80°C
5. PROTECTION: IP67 (WHEN MATED)
6. UL RECOGNIZED FILE: E152210
   CSA CERTIFIED FILE: LR6837
7. ALL DIMENSIONS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE.







SCALE 2:3

ITEM	DESCRIPTION	MATERIAL	FINISH	
13	LABEL	VINYL	BLACK/YELLOW	
12	COUPLING NUT, MALE	ZINC DIE CAST	BLACK	
11	CONTACT PIN, 18 AWG	BRASS	GOLD PLATED	
10	CONTACT PIN, 16 AWG	BRASS	GOLD PLATED	
9	INSERT, MALE, 5 POLE	TPE	GRAY	B
8	OVERMOLD	TPE	GRAY	B
7	COUPLING NUT, FEMALE	ZINC DIE CAST	BLACK	
6	FRICTION RING	NYLON	WHITE	
5	SOCKET SLEEVE	ST. STEEL		
4	CONTACT SOCKET, 18 AWG	BRASS	GOLD PLATED	
3	CONTACT SOCKET , 16 AWG	BRASS	GOLD PLATED	
2	INSERT, FEMALE, 5 POLE	TPE	GRAY	B
1	CABLE, DEV-NET, TRUNK, 18/2, 15/2	PVC JACKET	GRAY	

DOCUMENT STATUS | P1 | RELEASE DATE | 2020/10/23 | 13:29:13

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS
FA = 0
FC = 0
FP = 0
DIVISIONAL SYMBOLS

DIMENSION UNITS: INCH/MM | SCALE: 1.5:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

	MM	INCH
4 PLACES	±	±
3 PLACES	±	±
2 PLACES	±	±
1 PLACE	±	±
0 PLACES	±	±
ANGULAR TOL	± °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: ITEM 2, 8 & 9 WERE PVC & MATERIAL TABLE MODIFIED.

EC NO: 645633
DRWN: VBASUTHKARP 2020/05/22
CHK'D: RSTONE 2020/10/01
APPR: BWOODMAN 2020/10/23

INITIAL REVISION:
DRWN: RSTONE 2009/05/11
APPR: JFMURPHY 2009/05/15

molex

MINI-CHANGE CORDSET, A SIZE
5 POLE, MALE-FEMALE, 90/90 DEG, SINGLE KEY,
15/18 AWG, DEVICE NET

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
SD-130025-003	PSD	001	B

THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
	C-SIZE	130025	SEE TABLE	GENERAL MARKET	1 OF 1

FORMAT: Eng-lega-master-db-prod-C
REVISION: E
DATE: 2020/01/14