

Auxiliary Switch

HCD Series

1 NO / NC • SPDT / (2)SPDT circuit



Description

The HCD auxiliary switch is designed as an accessory to a 3-pole contactor and used to switch an auxiliary load below 10 amperes.

Features & Benefits

FEATURES	BENEFITS
One model fits all Hartland Controls 3-pole contactors	Reducing need for multiple switch models

Applications

- HVAC/R

Specifications

Power Terminal Connections	Single Unit Interlock Configuration (One on Each Side - Max of Two), SPDT Circuit: 0.250" quick connects; Single Unit Interlock Configuration (One on Each Side - Max of Two): #6-32 screw terminals
Arrangement	Single Unit Interlock Configuration: 1 NO/NC (break before make); SPDT Circuit (One switch per Side): SPDT: SPDT Circuit (Two Switched per Side): (2) SPDT
Mounting Method	Chassis mount

Certification & Compliance

UL 508	File No. E227250
--------	------------------

Auxiliary Switch

HCD Series

Ordering Information

LITTELFUSE CATALOG NUMBER	SPECIAL FUNCTION	CURRENT RATING	SPECIFICATION CONTACTOR FORM PER CIRCUIT	SPECIFICATION INPUT VOLTAGE	WEIGHT
CON-AUX300-1	SPDT circuit; two switches per DC contactor side	10 A	(2) SPDT	250 V	0.1 Lb
CON-AUX600	SPDT circuit; one switch per DC contactor side	10 A	SPDT	600 V	0.1 Lb
CON-AUX300-2	Single unit interlock configuration; one on each DP contactor side (max of two)	10 A	1 NO / 1 NC	250 V	0.1 Lb

Dimensions

LITTELFUSE CATALOG NUMBER	HEIGHT - IN.(MM)	LENGTH - IN. (MM)	WIDTH - IN. (MM)
CON-AUX300-1	2.95 (74.93)	0.682 (17.32)	1.945 (49.4)
CON-AUX600	2.515 (63.88)	0.682 (17.32)	1.945 (49.4)
CON-AUX300-2	3.677 (93.4)	0.689 (17.5)	1.803 (45.8)

Disclaimer Notice – Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/product-disclaimer.