



Representative Image

Catalog No. 2TLA050009R1413**Description: "MKEY9M, SOL NPT, 110V MET. FLEX KE"****UPC No 804325832526****Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes**

Mechanical Solenoid Safety interlock switch, rugged polyester housing and stainless steel head, electromagnetic lock (power to lock), 1800N holding force. 110VAC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 1x 1/2NPT conduit entry. Delivered with metal flex key.

Descriptors

Category	Safety Sensors, Switches, Locks & Gate Boxes
Type	Process Lock

Specifications

Product Class	Safety Locks & Process Locks
Product Main Type	MKey
Supply Voltage	110VAC
Outputs	Contact
Number of Outputs	2NC + 2NO
Degree of Protection	IP67

Classifications

ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions

Product Net Depth / Length	46 mm
Product Net Height	160 mm
Product Net Width	46 mm
Product Net Weight	0.603kg

Safety Information

Performance Level	Up to e
-------------------	---------

