

# Catalog No. 2TLA050206R1030

Description: "LINESTRONG3L, 4NC/2NO, NPT"

UPC No 804325609715

Home > Machine Safety > Emergency Stops & Pilot Devices

Rope Pull Emergency Stop, die cast housing , with 1/2NPT entry, 4NC + 2NO, for rope pull installation to the left, for spans up to 100m (1 rope pull) or 125m (2 rope pulls)



## Descriptors

|          |                                 |
|----------|---------------------------------|
| Category | Emergency Stops & Pilot Devices |
| Type     | Rope Pull                       |

## Specifications

|                      |                         |
|----------------------|-------------------------|
| Product Class        | E-Stops & Pilot Devices |
| Product Main Type    | LineStrong              |
| Outputs              | Contact                 |
| Degree of Protection | IP67                    |

## Classifications

|                |                                            |
|----------------|--------------------------------------------|
| ETIM 4         | EC002033 - Emergency stop pull cord switch |
| ETIM 5.0       | EC002033 - Emergency stop pull cord switch |
| ETIM 6.0       | EC002033 - Emergency stop pull cord switch |
| ETIM 7         | EC002033 - Emergency stop pull cord switch |
| ETIM 8 (Etim8) | EC002033 - Emergency stop pull cord switch |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Depth / Length | 92 mm  |
| Product Net Height         | 143 mm |
| Product Net Width          | 240 mm |
| Product Net Weight         | 1.1kg  |

## Safety Information

|                   |         |
|-------------------|---------|
| Performance Level | Up to e |
|-------------------|---------|

