



Catalog No. RMS312222CHLBR

Description: MTR STACK 2-225A 3PH3PH RNGL LVB 42-100K

UPC No 783164673630

Home > Modular Metering > ReliaMod > ReliaMod Meter Module

Descriptors

Category	ReliaMod Meter Module
----------	-----------------------

Specifications

Enclosure	N3R Outdoor
Meter Equipment Group (MEG) Approved	Yes
Socket Amperage	225 A
Main Phase Input	3-Phase
Socket Phase Output	3-Phase
Voltage	208Y/120V
Socket Type	Ringless
No of Sockets	2
Socket Factory Installed Jaw Configuration	7-Jaw
Socket Bypass	Lever
Horizontal Bus Amperage	1200 A
Tenant Neutral Lugs (Per each socket) AWG/kcmil Al/Cu	#6-300
Tenant Ground Lugs (Per each socket) AWG/kcmil Al/Cu	#14-2/0
Meter Module Tenant Breaker Provisions	Only Accepts 42-100 KAIC XT3 & XT4 Tenant Breakers
Additional Notes	For tenant breaker load lugs, please refer to breaker specifications
Height (Inches)	54.0
Depth (Inches)	9.7
Width (Inches)	19.6
Estimated Weight (lbs)	200